

SL3000UL AC HIGH-TRAFFIC COMMERCIAL SLIDE GATE OPERATOR

The first choice for heavy-traffic applications.



PRODUCT HIGHLIGHT
CONTINUOUS-DUTY,
High-Temperature Motor

RELIABLE

LEGACY ELITE HEAVY-DUTY COMMERCIAL GEAR-DRIVEN TRANSMISSION PROVIDES UNSURPASSED RELIABILITY.

LIMIT SWITCH DESIGN PROVIDES PRECISION LIMIT ACCURACY AND RELIABILITY.

SURGE SUPPRESSION PROVIDES INDUSTRIAL SURGE AND LIGHTNING PROTECTION AGAINST STRIKES UP TO 50 FEET AWAY.

WARRANTY 5 YEARS COMMERCIAL, 7 YEARS RESIDENTIAL.

SMART

myQ® TECHNOLOGY ENABLES YOU TO SECURELY CONTROL AND MONITOR YOUR GATE OPERATOR FROM ANYWHERE.*

WIRELESS DUAL-GATE COMMUNICATION SYNCHRONIZES GATE OPENING/CLOSING AND ELIMINATES EXPENSIVE DRIVEWAY TRENCHING COSTS.

SAFE AND SECURE

SECURITY+ 2.0® SAFEGUARDS FACILITY ACCESS WITH ROLLING CODE TECHNOLOGY, OPENING FOR REGISTERED DEVICES ONLY.

INHERENT REVERSING SENSOR DETECTS OBSTRUCTIONS AND REVERSES GATE WHEN CLOSING OR STOPS/REVERSES THE GATE WHEN OPENING.

PRE-MOTION WARNING ALARM ACTIVATES ON-BOARD ALARM 3 SECONDS PRIOR TO GATE MOTION.

MANUAL DISCONNECT WHEN UNLOCKED ALLOWS GATE TO BE OPERATED MANUALLY.

QUICK CLOSE AND ANTI-TAILGATE QUICKLY SECURE PROPERTY, PREVENTING UNAUTHORIZED ACCESS.

UL® LISTED GATE OPERATORS WITH MONITORED SAFETY ENTRAPMENT PROTECTION DEVICES.

*Cellular data or Wi-Fi® connection required. Test equipment regularly and follow safety instructions.

INCLUDED ACCESSORIES:

MONITORED RETRO-REFLECTIVE PHOTO EYE

Enhanced retro-reflective photo eye now with heater and wider beam, engineered to stay aligned; max. range: 50 ft.



LMRRUL

MONITORED SMALL PROFILE RESISTIVE EDGE

Pressure-sensitive edge stops and/or reverses gate when obstructed.



S505AL

SAFETY ADD-ONS:

MONITORED THROUGH-BEAM PHOTO EYES

Enhanced through-beam now with wider beam and heater for high performance in most environments; max. range: 90 ft.



LMTBUL

MONITORED WIRELESS EDGE KIT

Low-energy Bluetooth® connection between a LiftMaster Monitored Resistive Edge and the gate operator; max. range: 130 ft.**



LMWEKITU

MONITORED SAFETY ENTRAPMENT EDGES

Full line of Small, Large and Wraparound Profile Edges that sense obstructions.



EDGES

TOTAL SOLUTION ACCESSORIES:

TELEPHONE ENTRY FOR COMMERCIAL APPLICATIONS AND GATED COMMUNITIES

Mid-capacity telephone entry access control system with Versa XS 4.0 software.



EL2000SS

PLUG-IN LOOP DETECTOR

Prevents the gate from closing on a vehicle in the path; power efficient for maximum cycles on Battery Backup.



LOOPDETLM

**Wireless kit for up to 4 transmitters and 2 resistive edges per transmitter.

MASTERFUL ENGINEERING.

MECHANICS



- **Continuous-Duty Motor with Class H Insulation** Is Rated for High-Cycle, High-Temperature Applications (Available in 1/2 and 1 HP)
- **Operator Duty Rating:** Continuous Duty
- **Wormgear Reduction:** Commercial Oil-Bath Gearbox Providing 30:1 Wormgear Reduction
- **Chain:** #41 Black Oxide (25 ft. Supplied)

POWER



- **115V** Single-Phase
- **Accessory Power:** 24VDC 500mA Output
- 2 Auxiliary Outlets
- Optional Kit (3PHCONV) to Convert an Input Voltage of 208/240/480/575VAC to an Output Voltage of 115VAC

COMMERCIAL-GRADE DESIGN



- **Chassis:** Constructed with 1/4 in. black powder coated steel for rust prevention
- **Cover:** High-Density, UV-Resistant, 1-Piece Polyethylene Plastic for Excellent Heat and Corrosion Resistance
- **UL® Usage Classification:** I, II, III and IV
- **Operator Weight:** 140 lbs.

26.51"




18.14"

20.39"

[SL3000101UL AND SL3000501UL HAVE THE SAME DIMENSIONS]

CAPACITIES



TEMPERATURE SPECIFICATIONS



WITHOUT HEATER

-4°F (-20°C) to 140°F (60°C)

WITH OPTIONAL HEATER (HTRNB)

-40°F (-40°C) to 140°F (60°C)

GATE
TRAVEL
SPEED

12" per second

STANDARD FEATURES.

EXTERNAL ALARM RESET BUTTON

- Instantly Resets the Built-In Safety Alarm Siren

MECHANICAL LIMIT SYSTEM

- Maintains Accurate Gate Position Throughout Gate Travel, Even After Using Manual Disconnect

MONITORED SAFETY INPUTS

- 3 Main Board, 3 Expansion Board

SECURITY+ 2.0® ON-BOARD RADIO RECEIVER

- Up to 50 Remote Controls (Unlimited with 811LMX/813LMX)

LED DIAGNOSTIC DISPLAY

- Simplifies Installation and Troubleshooting

PROGRAMMABLE AUXILIARY RELAYS

- Make Adding Additional Features Easy

HOMELINK® COMPATIBLE

- Version 4.0 or Higher*

SUPPORT.



For Support Tools and Training Videos, Visit
LiftMasterTraining.com

For More Information on Gate Operators, Visit
LiftMaster.com/UL325Gates

To Find the Right Perimeter Access Solution for You, Visit
LiftMaster.com/Solution-Generator



Sales Support: 800.282.6225
Technical Support Center: 800.528.2806
To Order: 800.323.2276



*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.