



G.T. COMIS

RACCORDERIE EMILIANE


Via Nino Bixio, 12 - 44042 CENTO (FE) • tel. 051 904583 r.a. - fax 051 904243
e-mail gtcomis@gtcomis.it

SCHEMA TECNICA – Technical Sheet

ART. 152: Raccordo per tubo polietilene F con ghiera in ottone

Brass female straight fitting for PE pipe
with brass cap

- R E -



Materiale/Material: Ottone Giallo/Yellow Brass

Filettatura/Thread: UNI EN 10226-1 (ex iso 7/1)

Normativa/Norm : DM 174 06/04/2004

Codice - Code	Ø	DN	L mm	Conf. - Pack	
				🔧	📦
1200408	1/2"	20	37	10	200
1200409	3/4"	25	43	10	120
1200410	1"	32	52	10	70
1200412	1"1/4	40	59	1	50
1200414	1"1/2	50	64	1	30
1200413	2"	63	71	1	15

Ottone Giallo con O-Ring NBR, pressione massima d'esercizio: PN 25 da 1/2" a 3/4",
PN 16 da 1" a 2", temperatura d'esercizio: da 20 C a +110°C

Yellow brass with NBR O-ring, maximum working pressure: PN 25 from 1/2" to 3/4",
PN 16 from 1" to 2", operating temperature: from -20 C to +110°C