



G.T. COMIS

RACCORDERIE EMILIANE


Via Nino Bixio, 12 - 44042 CENTO (FE) • tel. 051 904583 r.a. - fax 051 904243
e-mail gtcomis@gtcomis.it

SCHEMA TECNICA – Technical Sheet

ART. 154: Manicotto per tubo polietilene con ghiera in ottone

Brass Straight fitting for PE pipe with
brass cap

- R E -



Materiale/Material: Ottone Giallo/Yellow Brass

Filettatura/Thread: UNI EN 10226-1 (ex iso 7/1)

Normativa/Norm : DM 174 06/04/2004

Codice - Code	Ø	L mm	Conf. - Pack	
			Ø	Box
1200608	20x20	53	10	120
1200609	25x25	63	10	80
1200610	32x32	70	10	50
1200611	40x40	77	1	30
1200612	50x50	97	1	15
1200613	63x63	107	1	10

Ottone Giallo con O-Ring NBR, pressione massima d'esercizio: PN 25 da 1/2" a 3/4",

PN 16 da 1" a 2", temperatura d'esercizio: da -20 C a +110°C

Yellow brass with NBR O-ring, maximum working pressure: PN 25 from 1/2" to 3/4",

PN 16 from 1" to 2", operating temperature: from -20 C to +110°C