



G.T. COMIS

RACCORDERIE EMILIANE


Via Nino Bixio, 12 - 44042 CENTO (FE) • tel. 051 904583 r.a. - fax 051 904243
e-mail gtcomis@gtcomis.it

SCHEMA TECNICA – Technical Sheet

ART. 160: Gomito per tubo polietilene con ghiera in ottone

Brass elbow fitting for PE pipe with
brass cap

- R E -



Materiale/Material: Ottone Giallo/Yellow Brass

Filettatura/Thread: UNI EN 10226-1 (ex iso 7/1)

Normativa/Norm: DM 174 06/04/2004

Codice - Code	Ø	A mm	Conf. - Pack	
			☺	📦
1201408	20x20	40	10	120
1201409	25x25	45,5	10	60
1201410	32x32	52,5	10	40
1201411	40x40	61,5	1	20
1201412	50x50	71	1	10
1201413	63x63	89	1	5

Ottone Giallo con O-Ring NBR, pressione massima d'esercizio: PN 25 da 1/2" a 3/4",
PN 16 da 1" a 2", temperatura d'esercizio: da -20 C a +110°C

Yellow brass with NBR O-ring, maximum working pressure: PN 25 from 1/2" to 3/4",
PN 16 from 1" to 2", working temperature: from -20 C to +110°C