



G.T. COMIS

RACCORDERIE EMILIANE


Via Nino Bixio, 12 - 44042 CENTO (FE) • tel. 051 904583 r.a. - fax 051 904243
e-mail gtcomis@gtcomis.it

SCHEMA TECNICA – Technical Sheet

ART. 162: Gomito F per tubo polietilene con ghiera in ottone

Brass female elbow fitting for PE pipe
with brass cap

- R E -



Materiale/Material: Ottone Giallo/Yellow Brass

Filettatura/Thread: UNI EN 10226-1 (ex iso 7/1)

Normativa/Norm: DM 174 06/04/2004

Codice - Code	Ø	A mm	B mm	Conf. - Pack	
1201808	20x1/2"	32	40	10	150
1201809	25x3/4"	35	45,5	10	80
1201810	32x1"	39	52,5	10	50
1201811	40x1 1/4"	43	60,5	1	30
1201812	50x1 1/2"	53	71,5	1	15
1201813	63x2"	62	83	1	10

Ottone Giallo con O-Ring NBR, pressione massima d'esercizio: PN 25 da 1/2" a 3/4",

PN 16 da 1" a 2", temperatura d'esercizio: da -20 C a +110°C

Yellow brass with NBR O-ring, maximum working pressure: PN 25 from 1/2" to 3/4",

PN 16 from 1" to 2", working temperature: from -20 C to +110°C