



**G.T. COMIS**

RACCORDERIE EMILIANE

Via Nino Bixio, 12 - 44042 CENTO (FE) • tel. 051 904583 r.a. - fax 051 904243  
e-mail gtcomis@gtcomis.it

## SCHEMA TECNICA – Technical Sheet

### **ART. 1894: Manometro attacco posteriore Ø50 cassa in ABS**


Back connection pressure gauge



**Materiale**/Material: contenitore in ABS,  
connettore in ottone/ABS case, brass connector

**Filettatura**/Thread: EN 837.1

**Classe di accuratezza**/Accuracy class: 2.5



| Codice - Code | attacco | Ø  | a<br>mm | b<br>mm | c<br>mm | bar  | Conf. - Pack<br> |
|---------------|---------|----|---------|---------|---------|------|-------------------------------------------------------------------------------------------------------|
| 2315405       | 1/4"    | 50 | 53      | 28,5    | 45,5    | 0-4  | 10                                                                                                    |
| 2315605       | 1/4"    | 50 | 53      | 28,5    | 45,5    | 0-6  | 10                                                                                                    |
| 2315607       | 1/4"    | 50 | 53      | 28,5    | 45,5    | 0-10 | 10                                                                                                    |



**G.T. COMIS**

RACCORDERIE EMILIANE

Via Nino Bixio, 12 - 44042 CENTO (FE) • tel. 051 904583 r.a. - fax 051 904243  
e-mail [gtcomis@gtcomis.it](mailto:gtcomis@gtcomis.it)

## SCHEMA TECNICA – Technical Sheet

### Manometri con cassa ABS | ABS pressure gauges

**Pressione ammissibile:**

- Statica:  $3/4$  x valore di fondo scala
- Fluttuante:  $2/3$  x valore di fondo scala
- Breve periodo: Valore di fondo scala

**Temperature consentite:**

- Ambiente:  $-20^{\circ} +60^{\circ} \text{ }^{\circ}\text{C}$
- Fluido: massimo  $+60^{\circ} \text{ }^{\circ}\text{C}$

**Materiale:**

- Connettore in ottone
- Elemento sensibile in bronzo fosforoso
- Cassa in ABS
- Movimento in lega di rame
- Vetro in PC
- Quadrante alluminio bianco con fermo a zero

**Pressure limitation:**

- Steady:  $3/4$  full scale value
- Fluctuating:  $2/3$  full scale value
- Short time: full scale value

**Working temperature:**

- Ambient:  $-20^{\circ} +60^{\circ} \text{ }^{\circ}\text{C}$
- Medium:  $+60^{\circ} \text{ }^{\circ}\text{C}$  maximum

**Materials:**

- Connection: brass
- Pressure element: Phosphor Bronze
- Case: ABS
- Movement: copper alloy
- Window: PC
- Dial: Aluminium, white, black lettering