



G.T. COMIS


RACCORDERIE EMILIANE

Via Nino Bixio, 12 - 44042 CENTO (FE) • tel. 051 904583 r.a. - fax 051 904243
e-mail gtcomis@gtcomis.it

SCHEMA TECNICA – Technical Sheet

ART. 1896: Manometro attacco posteriore Ø63 cassa in ABS

Back connection pressure gauge



Materiale/Material: contenitore in ABS,
connettore in ottone/ABS case, brass connector

Filettatura/Thread: EN 837.1

Classe di accuratezza/Accuracy class: 2.5

Codice - Code	attacco	Ø	a mm	b mm	c mm	bar	Conf. - Pack 
2315406	1/4"	63	63	29,5	47,5	0-4	10
2315606	1/4"	63	63	29,5	47,5	0-6	10
2316006	1/4"	63	63	29,5	47,5	0-10	10



G.T. COMIS

RACCORDERIE EMILIANE

Via Nino Bixio, 12 - 44042 CENTO (FE) • tel. 051 904583 r.a. - fax 051 904243
e-mail gtcomis@gtcomis.it

SCHEMA TECNICA – Technical Sheet

Manometri con cassa ABS | ABS pressure gauges

Pressione ammissibile:

- Statica: $3/4$ x valore di fondo scala
- Fluttuante: $2/3$ x valore di fondo scala
- Breve periodo: Valore di fondo scala

Temperature consentite:

- Ambiente: $-20^{\circ} +60^{\circ} \text{ }^{\circ}\text{C}$
- Fluido: massimo $+60^{\circ} \text{ }^{\circ}\text{C}$

Materiale:

- Connettore in ottone
- Elemento sensibile in bronzo fosforoso
- Cassa in ABS
- Movimento in lega di rame
- Vetro in PC
- Quadrante alluminio bianco con fermo a zero

Pressure limitation:

- Steady: $3/4$ full scale value
- Fluctuating: $2/3$ full scale value
- Short time: full scale value

Working temperature:

- Ambient: $-20^{\circ} +60^{\circ} \text{ }^{\circ}\text{C}$
- Medium: $+60^{\circ} \text{ }^{\circ}\text{C}$ maximum

Materials:

- Connection: brass
- Pressure element: Phosphor Bronze
- Case: ABS
- Movement: copper alloy
- Window: PC
- Dial: Aluminium, white, black lettering