



G.T. COMIS

RACCORDERIE EMILIANE

Via Nino Bixio, 12 - 44042 CENTO (FE) • tel. 051 904583 r.a. - fax 051 904243
e-mail gtcomis@gtcomis.it

SCHEMA TECNICA – Technical Sheet

ART. 932: Manometro con glicerina attacco radiale, cassa inox Ø100

Radial connection pressure gauge with
glycerine




Materiale/Material: AISI 304 (1,4301),

connettore in ottone/ brass connector

Filettatura/Thread: EN 837.1

Classe di accuratezza/Accuracy class: 1.0



Codice - Code	Attacco	Cassa Ø	a mm	b mm	c mm	bar	Conf. - Pack 	
NEW 2300740	1/2"	Ø100	108,5	83	35,5	-1 - 0	10	50
NEW 2300743	1/2"	Ø100	108,5	83	35,5	0-4	10	50
NEW 2300744	1/2"	Ø100	108,5	83	35,5	0-6	10	50
NEW 2300745	1/2"	Ø100	108,5	83	35,5	0-10	10	50
NEW 2300746	1/2"	Ø100	108,5	83	35,5	0-12	10	50
NEW 2300747	1/2"	Ø100	108,5	83	35,5	0-16	10	50
NEW 2300748	1/2"	Ø100	108,5	83	35,5	0-25	10	50
NEW 2300749	1/2"	Ø100	108,5	83	35,5	0-40	10	50
NEW 2300750	1/2"	Ø100	108,5	83	35,5	0-60	10	50
NEW 2300751	1/2"	Ø100	108,5	83	35,5	0-100	10	50
NEW 2300752	1/2"	Ø100	108,5	83	35,5	0-160	10	50
NEW 2300753	1/2"	Ø100	108,5	83	35,5	0-250	10	50
NEW 2300754	1/2"	Ø100	108,5	83	35,5	0-400	10	50
NEW 2300755	1/2"	Ø100	108,5	83	35,5	0-600	10	50



G.T. COMIS

RACCORDERIE EMILIANE

Via Nino Bixio, 12 - 44042 CENTO (FE) • tel. 051 904583 r.a. - fax 051 904243
e-mail gtcomis@gtcomis.it

SCHEMA TECNICA – Technical Sheet

Manometri con glicerina | Pressure gauge with glycerine

Pressione ammissibile:

- Statica: 3/4 x valore di fondo scala
- Fluttuante: 2/3 x valore di fondo scala
- Breve periodo: Valore di fondo scala

Temperature consentite:

- Ambiente: -5° +60 °C
- Fluido: massimo +60 °C

Materiale:

- Connettore in ottone
- Elemento sensibile in bronzo fosforoso
- Cassa in Acciaio Inox AISI 304 (1.4301)
- Movimento in lega di rame
- Vetro in PC
- Quadrante alluminio bianco con fermo a zero

Pressure limitation:

- Steady: 3/4 full scale value
- Fluctuating: 2/3 full scale value
- Short time: full scale value

Working temperature:

- Ambient: -5° +60 °C with glycerine filling
- Medium: +60 °C maximum

Materials:

- Connection: brass
- Pressure element: Phosphor Bronze
- Case: SS AISI 304 (1.4301)
- Movement: copper alloy
- Window: PC
- Dial: Aluminium, white, black lettering