

MARINE SHIELD UV SAIL FLEX PART A

Version No: 1.3.7.11
Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: 04/03/2025
Print Date: 15/11/2023
L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	MARINE SHIELD UV SAIL FLEX PART A
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	10697
--------------------------	-------

Details of the supplier of the safety data sheet

Registered company name	Super Sail Marine Shield Limited
Address	322 Mangapai Road. RD 8. Whangarei. 0178 New Zealand
Telephone	+64 21 067 1634
Fax	
Website	www.marineshield.co.nz
Email	info@marineshield.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7days)	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	0800 764766	+61 2 9186 1132
Other emergency telephone numbers	Not Available	+64 800 700 112

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification [1]	Flammable Liquids Category 3, Sensitisation (Respiratory) Category 1, Specific Target Organ Toxicity - Single Exposure Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2, Skin Corrosion/Irritation Category 2, Reproductive Toxicity Category 2, Sensitisation (Skin) Category 1, Carcinogenicity Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	3.1C, 6.3A, 6.5A (respiratory), 6.5B (contact), 6.7B, 6.8B, 6.9B, 9.1C

Label elements

Hazard pictogram(s)	 
Signal word	Danger

Hazard statement(s)

H226	Flammable liquid and vapour.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H371	May cause damage to organs. (Oral, Dermal, Inhalation)
H373	May cause damage to organs through prolonged or repeated exposure. (Oral, Dermal, Inhalation)
H315	Causes skin irritation.
H361	Suspected of damaging fertility or the unborn child.

MARINE SHIELD UV SAIL FLEX PART A

H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves and protective clothing.
P284	[In case of inadequate ventilation] wear respiratory protection.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P264	Wash all exposed external body areas thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician/first aider.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P302+P352	IF ON SKIN: Wash with plenty of water.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor/physician/first aider.
P314	Get medical advice/attention if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Ingredients are required by the Hazard Substances (Safety Data Sheets) Notice 2017, EPA consolidation 30 April 2021 to be identified:

Mixtures

CAS No	%[weight]	Name
4083-64-1	0.1-1	<u>p-toluenesulfonyl isocyanate</u>
1330-20-7	5-15	<u>xylene</u>
95-14-7	0.1-1	benzotriazol derivatives
100-41-4	0.1-1	<u>ethylbenzene</u>
64742-48-9.	1-10	<u>naphtha_petroleum_hydrodesulfurised heavy</u>
64742-49-0.	1-10	<u>naphtha petroleum, light, hydrotreated</u>
120-55-8	1-10	<u>diethylene glycol dibenzoate</u>
108-65-6	1-10	<u>propylene glycol monomethyl ether - mixture of isomers</u>
763-69-9	1-20	<u>ethyl-3-ethoxypropionate</u>
822-06-0	0.1-1	<u>hexamethylene diisocyanate</u>
28182-81-2	1-20	<u>hexamethylene diisocyanate polymer</u>
122-99-6	0.1-1	<u>ethylene glycol phenyl ether</u>
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available	

SECTION 4 First aid measures

MARINE SHIELD UV SAIL FLEX PART A

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: - Wash out immediately with fresh running water. - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. - Seek medical attention without delay; if pain persists or recurs seek medical attention. - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: - Immediately remove all contaminated clothing, including footwear. - Flush skin and hair with running water (and soap if available). - Seek medical attention in event of irritation.
Inhalation	If fumes, aerosols or combustion products are inhaled remove from contaminated area.
Ingestion	- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus. If swallowed do NOT induce vomiting. - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. - Observe the patient carefully. - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. - Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For sub-chronic and chronic exposures to isocyanates:

- This material may be a potent pulmonary sensitiser which causes bronchospasm even in patients without prior airway hyperreactivity.
- Clinical symptoms of exposure involve mucosal irritation of respiratory and gastrointestinal tracts.
- Conjunctival irritation, skin inflammation (erythema, pain vesiculation) and gastrointestinal disturbances occur soon after exposure.
- Pulmonary symptoms include cough, burning, substernal pain and dyspnoea.
- Some cross-sensitivity occurs between different isocyanates.
- Noncardiogenic pulmonary oedema and bronchospasm are the most serious consequences of exposure. Markedly symptomatic patients should receive oxygen, ventilatory support and an intravenous line.
- Treatment for asthma includes inhaled sympathomimetics (epinephrine [adrenalin], terbutaline) and steroids.
- Activated charcoal (1 g/kg) and a cathartic (sorbitol, magnesium citrate) may be useful for ingestion.
- Mydriatics, systemic analgesics and topical antibiotics (Sulamyd) may be used for corneal abrasions.
- There is no effective therapy for sensitised workers.

[Ellenhorn and Barceloux; Medical Toxicology]

NOTE: Isocyanates cause airway restriction in naive individuals with the degree of response dependant on the concentration and duration of exposure. They induce smooth muscle contraction which leads to bronchoconstrictive episodes. Acute changes in lung function, such as decreased FEV1, may not represent sensitivity.

[Karol & Jin, Frontiers in Molecular Toxicology, pp 56-61, 1992]

Personnel who work with isocyanates, isocyanate prepolymers or polyisocyanates should have a pre-placement medical examination and periodic examinations thereafter, including a pulmonary function test. Anyone with a medical history of chronic respiratory disease, asthmatic or bronchial attacks, indications of allergic responses, recurrent eczema or sensitisation conditions of the skin should not handle or work with isocyanates. Anyone who develops chronic respiratory distress when working with isocyanates should be removed from exposure and examined by a physician. Further exposure must be avoided if a sensitivity to isocyanates or polyisocyanates has developed.

For acute or short term repeated exposures to xylene:

- Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
- Pulmonary absorption is rapid with about 60-65% retained at rest.
- Primary threat to life from ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases ($pO_2 < 50$ mm Hg or $pCO_2 > 50$ mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
Methylhippuric acids in urine	1.5 gm/gm creatinine	End of shift	
	2 mg/min	Last 4 hrs of shift	

SECTION 5 Firefighting measures

Extinguishing media

- Small quantities of water in contact with hot liquid may react violently with generation of a large volume of rapidly expanding hot sticky semi-solid foam.
- Alcohol stable foam.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

Advice for firefighters

Fire Fighting	Alert Fire Brigade and tell them location and nature of hazard.
---------------	---

MARINE SHIELD UV SAIL FLEX PART A

Fire/Explosion Hazard	▶ Liquid and vapour are flammable. Combustion products include: carbon dioxide (CO2) carbon monoxide (CO) isocyanates hydrogen cyanide and minor amounts of nitrogen oxides (NOx) other pyrolysis products typical of burning organic material.
-----------------------	--

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Remove all ignition sources. Contain spill with inert non- combustible absorbent then place in suitable, labelled container for waste disposal. Wipe up. Clean area with large quantity of water to complete clean- up.
Major Spills	Remove all ignition sources. Clear area of personnel and move upwind. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non- combustible material onto spillage. Use clean non- sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authority. ▶ Liquid Isocyanates and high isocyanate vapour concentrations will penetrate seals on self contained breathing apparatus - SCBA should be used inside encapsulating suit where this exposure may occur. For isocyanate spills of less than 40 litres (2 m2): ▶ Evacuate area from everybody not dealing with the emergency, keep them upwind and prevent further access, remove ignition sources and, if inside building, ventilate area as well as possible. ▶ Avoid contamination with water, alkalies and detergent solutions.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▶ Containers, even those that have been emptied, may contain explosive vapours. ▶ Electrostatic discharge may be generated during pumping - this may result in fire. ▶ Avoid unnecessary personal contact, including inhalation. ▶ DO NOT allow clothing wet with material to stay in contact with skin
Other information	▶ Store in original containers in approved flammable liquid storage area. for commercial quantities of isocyanates: -Isocyanates should be stored in adequately bunded areas.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Packing as supplied by manufacturer. ▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type.
Storage incompatibility	▶ avoid contact with strong oxidisers, alcohols and acids ▶ attack some plastics, rubber and coatings

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	p-toluenesulfonyl isocyanate	Isocyanates, all, (as -NCO)	0.02 mg/m3	0.07 mg/m3	Not Available	dsen-Dermal sensitiser (rsen)-Respiratory sensitiser Note: These values apply to all isocyanates, including prepolymers, present in the workplace air as vapours, mist or dust.
New Zealand Workplace Exposure Standards (WES)	xylene	Dimethylbenzene	50 ppm / 217 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	ethylbenzene	Ethyl benzene	100 ppm / 434 mg/m3	543 mg/m3 / 125 ppm	Not Available	Not Available

MARINE SHIELD UV SAIL FLEX PART A

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	naphtha, petroleum, hydrodesulfurised heavy	Rubber solvent (Naphtha)	400 ppm / 1600 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	naphtha, petroleum, hydrodesulfurised heavy	White spirits (Stoddard solvent)	100 ppm / 525 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	propylene glycol monomethyl ether - mixture of isomers	Propylene glycol monomethyl ether	100 ppm / 369 mg/m3	553 mg/m3 / 150 ppm	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	hexamethylene diisocyanate	Hexamethylene diisocyanate	0.02 mg/m3	0.07 mg/m3	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	hexamethylene diisocyanate polymer	Isocyanates, all, (as -NCO)	0.02 mg/m3	0.07 mg/m3	Not Available	dsen-Dermal sensitiser (rsen)-Respiratory sensitiser Note: These values apply to all isocyanates, including prepolymers, present in the workplace air as vapours, mist or dust.

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
xylene	Not Available	Not Available	Not Available
ethylbenzene	Not Available	Not Available	Not Available
naphtha, petroleum, hydrodesulfurised heavy	350 mg/m3	1,800 mg/m3	40,000 mg/m3
naphtha, petroleum, hydrodesulfurised heavy	1,200 mg/m3	6,700 mg/m3	40,000 mg/m3
naphtha, petroleum, hydrodesulfurised heavy	1,200 mg/m3	6,700 mg/m3	40,000 mg/m3
naphtha, petroleum, hydrodesulfurised heavy	1,100 mg/m3	1,800 mg/m3	40,000 mg/m3
naphtha, petroleum, hydrodesulfurised heavy	1,200 mg/m3	6,700 mg/m3	40,000 mg/m3
naphtha, petroleum, hydrodesulfurised heavy	1,100 mg/m3	1,800 mg/m3	40,000 mg/m3
naphtha, petroleum, hydrodesulfurised heavy	300 mg/m3	1,800 mg/m3	29500** mg/m3
naphtha petroleum, light, hydrotreated	1,000 mg/m3	11,000 mg/m3	66,000 mg/m3
propylene glycol monomethyl ether - mixture of isomers	100 ppm	160 ppm	660 ppm
propylene glycol monomethyl ether - mixture of isomers	Not Available	Not Available	Not Available
ethyl-3-ethoxypropionate	1.6 ppm	18 ppm	110 ppm
hexamethylene diisocyanate	0.018 ppm	0.2 ppm	3 ppm
hexamethylene diisocyanate polymer	7.8 mg/m3	86 mg/m3	510 mg/m3
ethylene glycol phenyl ether	1.5 ppm	16 ppm	97 ppm

Ingredient	Original IDLH	Revised IDLH
p-toluenesulfonyl isocyanate	Not Available	Not Available
xylene	900 ppm	Not Available
ethylbenzene	800 ppm	Not Available
naphtha, petroleum, hydrodesulfurised heavy	20,000 mg/m3 / 1,100 ppm / 1,000 ppm	Not Available
naphtha petroleum, light, hydrotreated	Not Available	Not Available
diethylene glycol dibenzoate	Not Available	Not Available
propylene glycol monomethyl ether - mixture of isomers	Not Available	Not Available
ethyl-3-ethoxypropionate	Not Available	Not Available
hexamethylene diisocyanate	Not Available	Not Available
hexamethylene diisocyanate polymer	Not Available	Not Available
ethylene glycol phenyl ether	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
naphtha petroleum, light,	E	≤ 0.1 ppm

Notes: Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

MARINE SHIELD UV SAIL FLEX PART A

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
hydrotreated		
ethyl-3-ethoxypropionate	E	≤ 0.1 ppm
ethylene glycol phenyl ether	E	≤ 0.1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

MATERIAL DATA

IFRA Prohibited Fragrance Substance

The International Fragrance Association (IFRA) Standards form the basis for the globally accepted and recognized risk management system for the safe use of fragrance ingredients and are part of the IFRA Code of Practice.

for isocyanates:

Some jurisdictions require that health surveillance be conducted on occupationally exposed workers.

for heptane (all isomers)

The TLV-TWA is protective against narcotic and irritant effects which are greater than those of pentane or n-hexane but less than those of octane.

for propylene glycol monomethyl ether (PGME)

Odour Threshold: 10 ppm.

for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially.

for ethyl benzene:

Odour Threshold Value: 0.46-0.60 ppm

NOTE: Detector tubes for ethylbenzene, measuring in excess of 30 ppm, are commercially available.

for 1,6-hexamethylene diisocyanate (HDI):

The toxicological action of HDI is similar to that of toluene diisocyanate and the TLV-TWA is analogous.

NOTE P: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0.01% w/w benzene (EINECS No 200-753-7).

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. ▶ All processes in which isocyanates are used should be enclosed wherever possible.
Personal protection	
Eye and face protection	▶ Safety glasses with side shields.
Skin protection	See Hand protection below
Hands/feet protection	NOTE: ▶ The material may produce skin sensitisation in predisposed individuals. For esters: ▶ Do NOT use natural rubber, butyl rubber, EPDM or polystyrene-containing materials. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. ▶ Do NOT wear natural rubber (latex gloves). ▶ Isocyanate resistant materials include Teflon, Viton, nitrile rubber and some PVA gloves. ▶ DO NOT use skin cream unless necessary and then use only minimum amount.
Body protection	See Other protection below
Other protection	All employees working with isocyanates must be informed of the hazards from exposure to the contaminant and the precautions necessary to prevent damage to their health. ▶ Overalls. ▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.

Respiratory protection

Full face respirator with supplied air.

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

For spraying or operations which might generate aerosols:

Full face respirator with supplied air.

- ▶ In certain circumstances, personal protection of the individual employee is necessary. Personal protective devices should be regarded as being supplementary to substitution and engineering control and should not be used in preference to them as they do nothing to eliminate the hazard.
- ▶ However, in some situations, minimising exposure to isocyanates by enclosure and ventilation is not possible, and occupational exposure standards may be exceeded, particularly during on-site mixing of paints, spray-painting, foaming and maintenance of machine and ventilation systems. In these situations, air-line respirators or self-contained breathing apparatus complying with the appropriate national standard must be used.
- ▶ **Organic vapour respirators with particulate pre-filters and powered, air-purifying respirators are NOT suitable.**
- ▶ Personal protective equipment must be appropriately selected, individually fitted and workers trained in their correct use and maintenance. Personal protective equipment must be regularly checked and maintained to ensure that the worker is being protected.
- ▶ Air-line respirators or self-contained breathing apparatus complying with the appropriate national standard should be used during the clean-up of spills and the repair or clean-up of contaminated equipment and similar situations which cause emergency exposures to hazardous atmospheric concentrations of isocyanate.

Continued...

MARINE SHIELD UV SAIL FLEX PART A

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid		
Physical state	Liquid	Relative density (Water = 1)	1.0
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	345
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	70
Initial boiling point and boiling range (°C)	147	Molecular weight (g/mol)	Not Available
Flash point (°C)	41	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	9.8	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1.0	Volatile Component (%vol)	51.4
Vapour pressure (kPa)	1.20	Gas group	Not Available
Solubility in water	Reacts	pH as a solution (%)	Not Available
Vapour density (Air = 1)	4.56	VOC g/L	453

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	► Stable
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. The main effects of simple aliphatic esters are narcosis and irritation and anaesthesia at higher concentrations. The vapour/mist may be highly irritating to the upper respiratory tract and lungs; the response may be severe enough to produce bronchitis and pulmonary oedema. Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. The acute toxicity of inhaled alkylbenzenes is best described by central nervous system depression.
Ingestion	Swallowing of the liquid may cause aspiration of vomit into the lungs with the risk of haemorrhaging, pulmonary oedema, progressing to chemical pneumonitis; serious consequences may result.
Skin Contact	The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. The material may produce mild skin irritation; limited evidence or practical experience suggests, that the material either: ► produces mild inflammation of the skin in a substantial number of individuals following direct contact, and/or ► produces significant, but mild, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.
Eye	Limited evidence or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals. The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis.

MARINE SHIELD UV SAIL FLEX PART A

Chronic	On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment. Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems. Practical evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a substantial number of individuals at a greater frequency than would be expected from the response of a normal population. Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals. There is sufficient evidence to provide a strong presumption that human exposure to the material may result in impaired fertility on the basis of: - clear evidence in animal studies of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects but which is not a secondary non-specific consequence of other toxic effects. Polyisocyanates still contain small amounts of monomeric isocyanate (typically <0.5 parts per weight) and both – the polyisocyanate and the monomer - have toxicological importance. Persons with a history of asthma or other respiratory problems or are known to be sensitised, should not be engaged in any work involving the handling of isocyanates. Repeated application of mildly hydrotreated oils (principally paraffinic), to mouse skin, induced skin tumours; no tumours were induced with severely hydrotreated oils. Prolonged or repeated contact with xylenes may cause defatting dermatitis with drying and cracking.														
MARINE SHIELD UV SAIL FLEX PART A	<table> <tr> <th data-bbox="389 656 938 683">TOXICITY</th><th data-bbox="938 656 1489 683">IRRITATION</th></tr> <tr> <td data-bbox="389 683 938 723">Not Available</td><td data-bbox="938 683 1489 723">Not Available</td></tr> </table>	TOXICITY	IRRITATION	Not Available	Not Available										
TOXICITY	IRRITATION														
Not Available	Not Available														
p-toluenesulfonyl isocyanate	<table> <tr> <th data-bbox="389 768 1174 795">TOXICITY</th><th data-bbox="1174 768 1489 795">IRRITATION</th></tr> <tr> <td data-bbox="389 795 1174 835">dermal (rat) LD50: >2000 mg/kg^[1]</td><td data-bbox="1174 795 1489 835">Not Available</td></tr> <tr> <td data-bbox="389 835 1174 875">Inhalation(Rat) LC50; >320 ppm4h^[2]</td><td data-bbox="1174 835 1489 875"></td></tr> <tr> <td data-bbox="389 875 1174 916">Oral(Rat) LD50; 2234 mg/kg^[2]</td><td data-bbox="1174 875 1489 916"></td></tr> </table>	TOXICITY	IRRITATION	dermal (rat) LD50: >2000 mg/kg ^[1]	Not Available	Inhalation(Rat) LC50; >320 ppm4h ^[2]		Oral(Rat) LD50; 2234 mg/kg ^[2]							
TOXICITY	IRRITATION														
dermal (rat) LD50: >2000 mg/kg ^[1]	Not Available														
Inhalation(Rat) LC50; >320 ppm4h ^[2]															
Oral(Rat) LD50; 2234 mg/kg ^[2]															
xylene	<table> <tr> <th data-bbox="389 960 938 987">TOXICITY</th><th data-bbox="938 960 1489 987">IRRITATION</th></tr> <tr> <td data-bbox="389 987 938 1028">Dermal (rabbit) LD50: >1700 mg/kg^[2]</td><td data-bbox="938 987 1489 1028">Eye (human): 200 ppm irritant</td></tr> <tr> <td data-bbox="389 1028 938 1068">Inhalation(Rat) LC50; 5922 ppm4h^[1]</td><td data-bbox="938 1028 1489 1068">Eye (rabbit): 5 mg/24h SEVERE</td></tr> <tr> <td data-bbox="389 1068 938 1108">Oral(Mouse) LD50; 2119 mg/kg^[2]</td><td data-bbox="938 1068 1489 1108">Eye (rabbit): 87 mg mild</td></tr> <tr> <td data-bbox="389 1108 938 1149"></td><td data-bbox="938 1108 1489 1149">Eye: adverse effect observed (irritating)^[1]</td></tr> <tr> <td data-bbox="389 1149 938 1189"></td><td data-bbox="938 1149 1489 1189">Skin (rabbit):500 mg/24h moderate</td></tr> <tr> <td data-bbox="389 1189 938 1218"></td><td data-bbox="938 1189 1489 1218">Skin: adverse effect observed (irritating)^[1]</td></tr> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: >1700 mg/kg ^[2]	Eye (human): 200 ppm irritant	Inhalation(Rat) LC50; 5922 ppm4h ^[1]	Eye (rabbit): 5 mg/24h SEVERE	Oral(Mouse) LD50; 2119 mg/kg ^[2]	Eye (rabbit): 87 mg mild		Eye: adverse effect observed (irritating) ^[1]		Skin (rabbit):500 mg/24h moderate		Skin: adverse effect observed (irritating) ^[1]
TOXICITY	IRRITATION														
Dermal (rabbit) LD50: >1700 mg/kg ^[2]	Eye (human): 200 ppm irritant														
Inhalation(Rat) LC50; 5922 ppm4h ^[1]	Eye (rabbit): 5 mg/24h SEVERE														
Oral(Mouse) LD50; 2119 mg/kg ^[2]	Eye (rabbit): 87 mg mild														
	Eye: adverse effect observed (irritating) ^[1]														
	Skin (rabbit):500 mg/24h moderate														
	Skin: adverse effect observed (irritating) ^[1]														
ethylbenzene	<table> <tr> <th data-bbox="389 1252 938 1279">TOXICITY</th><th data-bbox="938 1252 1489 1279">IRRITATION</th></tr> <tr> <td data-bbox="389 1279 938 1319">Dermal (rabbit) LD50: >5000 mg/kg^[2]</td><td data-bbox="938 1279 1489 1319">Eye (rabbit): 500 mg - SEVERE</td></tr> <tr> <td data-bbox="389 1319 938 1359">Inhalation(Rat) LC50; 17.2 mg/l4h^[2]</td><td data-bbox="938 1319 1489 1359">Eye: no adverse effect observed (not irritating)^[1]</td></tr> <tr> <td data-bbox="389 1359 938 1400">Oral(Rat) LD50; ~3523 mg/kg^[2]</td><td data-bbox="938 1359 1489 1400">Skin (rabbit): 15 mg/24h mild</td></tr> <tr> <td data-bbox="389 1400 938 1442"></td><td data-bbox="938 1400 1489 1442">Skin: no adverse effect observed (not irritating)^[1]</td></tr> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: >5000 mg/kg ^[2]	Eye (rabbit): 500 mg - SEVERE	Inhalation(Rat) LC50; 17.2 mg/l4h ^[2]	Eye: no adverse effect observed (not irritating) ^[1]	Oral(Rat) LD50; ~3523 mg/kg ^[2]	Skin (rabbit): 15 mg/24h mild		Skin: no adverse effect observed (not irritating) ^[1]				
TOXICITY	IRRITATION														
Dermal (rabbit) LD50: >5000 mg/kg ^[2]	Eye (rabbit): 500 mg - SEVERE														
Inhalation(Rat) LC50; 17.2 mg/l4h ^[2]	Eye: no adverse effect observed (not irritating) ^[1]														
Oral(Rat) LD50; ~3523 mg/kg ^[2]	Skin (rabbit): 15 mg/24h mild														
	Skin: no adverse effect observed (not irritating) ^[1]														
naphtha, petroleum, hydrodesulfurised heavy	<table> <tr> <th data-bbox="389 1476 938 1503">TOXICITY</th><th data-bbox="938 1476 1489 1503">IRRITATION</th></tr> <tr> <td data-bbox="389 1503 938 1543">Dermal (rabbit) LD50: >1900 mg/kg^[1]</td><td data-bbox="938 1503 1489 1543">Eye: no adverse effect observed (not irritating)^[1]</td></tr> <tr> <td data-bbox="389 1543 938 1583">Inhalation(Rat) LC50; >1.58 mg/l4h^[1]</td><td data-bbox="938 1543 1489 1583">Skin: adverse effect observed (irritating)^[1]</td></tr> <tr> <td data-bbox="389 1583 938 1635">Oral(Rat) LD50; >4500 mg/kg^[1]</td><td data-bbox="938 1583 1489 1635">Skin: no adverse effect observed (not irritating)^[1]</td></tr> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	Inhalation(Rat) LC50; >1.58 mg/l4h ^[1]	Skin: adverse effect observed (irritating) ^[1]	Oral(Rat) LD50; >4500 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]						
TOXICITY	IRRITATION														
Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]														
Inhalation(Rat) LC50; >1.58 mg/l4h ^[1]	Skin: adverse effect observed (irritating) ^[1]														
Oral(Rat) LD50; >4500 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]														
naphtha petroleum, light, hydrotreated	<table> <tr> <th data-bbox="389 1668 938 1695">TOXICITY</th><th data-bbox="938 1668 1489 1695">IRRITATION</th></tr> <tr> <td data-bbox="389 1695 938 1736">Dermal (rabbit) LD50: >1900 mg/kg^[1]</td><td data-bbox="938 1695 1489 1736">Eye: no adverse effect observed (not irritating)^[1]</td></tr> <tr> <td data-bbox="389 1736 938 1776">Inhalation(Rat) LC50; >4.42 mg/L4h^[1]</td><td data-bbox="938 1736 1489 1776">Skin: adverse effect observed (irritating)^[1]</td></tr> <tr> <td data-bbox="389 1776 938 1827">Oral(Rat) LD50; >2000 mg/kg^[1]</td><td data-bbox="938 1776 1489 1827"></td></tr> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	Inhalation(Rat) LC50; >4.42 mg/L4h ^[1]	Skin: adverse effect observed (irritating) ^[1]	Oral(Rat) LD50; >2000 mg/kg ^[1]							
TOXICITY	IRRITATION														
Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]														
Inhalation(Rat) LC50; >4.42 mg/L4h ^[1]	Skin: adverse effect observed (irritating) ^[1]														
Oral(Rat) LD50; >2000 mg/kg ^[1]															
diethylene glycol dibenzoate	<table> <tr> <th data-bbox="389 1861 938 1888">TOXICITY</th><th data-bbox="938 1861 1489 1888">IRRITATION</th></tr> <tr> <td data-bbox="389 1888 938 1928">dermal (rat) LD50: >2000 mg/kg^[1]</td><td data-bbox="938 1888 1489 1928">Eye (rabbit): 500 mg/24h-mild</td></tr> <tr> <td data-bbox="389 1928 938 1968">Inhalation(Rat) LC50; >200 mg/l4h^[1]</td><td data-bbox="938 1928 1489 1968">Eye: no adverse effect observed (not irritating)^[1]</td></tr> <tr> <td data-bbox="389 1968 938 2009">Oral(Rat) LD50; 3535 mg/kg^[1]</td><td data-bbox="938 1968 1489 2009">Skin (rabbit): 500 mg/24h-mild</td></tr> <tr> <td data-bbox="389 2009 938 2051"></td><td data-bbox="938 2009 1489 2051">Skin: no adverse effect observed (not irritating)^[1]</td></tr> </table>	TOXICITY	IRRITATION	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 500 mg/24h-mild	Inhalation(Rat) LC50; >200 mg/l4h ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	Oral(Rat) LD50; 3535 mg/kg ^[1]	Skin (rabbit): 500 mg/24h-mild		Skin: no adverse effect observed (not irritating) ^[1]				
TOXICITY	IRRITATION														
dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 500 mg/24h-mild														
Inhalation(Rat) LC50; >200 mg/l4h ^[1]	Eye: no adverse effect observed (not irritating) ^[1]														
Oral(Rat) LD50; 3535 mg/kg ^[1]	Skin (rabbit): 500 mg/24h-mild														
	Skin: no adverse effect observed (not irritating) ^[1]														
propylene glycol monomethyl ether - mixture of isomers	<table> <tr> <th data-bbox="389 2085 938 2112">TOXICITY</th><th data-bbox="938 2085 1489 2112">IRRITATION</th></tr> <tr> <td data-bbox="389 2112 938 2161">dermal (rat) LD50: >2000 mg/kg^[1]</td><td data-bbox="938 2112 1489 2161">Eye (rabbit) 230 mg mild</td></tr> </table>	TOXICITY	IRRITATION	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit) 230 mg mild										
TOXICITY	IRRITATION														
dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit) 230 mg mild														

MARINE SHIELD UV SAIL FLEX PART A

	Oral(Rat) LD50; 5155 mg/kg ^[1]	Eye (rabbit) 500 mg/24 h. - mild
		Eye: no adverse effect observed (not irritating) ^[1]
		Skin (rabbit) 500 mg open - mild
		Skin: no adverse effect observed (not irritating) ^[1]
ethyl-3-ethoxypropionate	TOXICITY	IRRITATION
	dermal (guinea pig) LD50: >19 mg/kg ^[2]	Eye (rabbit): 500mg/24h - mild
	Inhalation(Rat) LC50; 1250 ppm4h ^[2]	Skin (rabbit):10 mg/24h open mild
	Oral(Rat) LD50; ~3200-5000 mg/kg ^[2]	
hexamethylene diisocyanate	TOXICITY	IRRITATION
	dermal (rat) LD50: >525 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]
	Inhalation(Rat) LC50; 0.124 mg/L4h ^[1]	Skin: adverse effect observed (corrosive) ^[1]
	Oral(Mouse) LD50; 350 mg/kg ^[2]	Skin: adverse effect observed (irritating) ^[1]
hexamethylene diisocyanate polymer	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Skin (rabbit): 500 mg - moderate
	Inhalation(Rat) LC50; 0.052-0.5 mg/L4h ^[1]	
	Oral(Rat) LD50; >2000 mg/kg ^[1]	
ethylene glycol phenyl ether	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2214 mg/kg ^[1]	Eye (rabbit): 250 ug/24h - SEVERE
	Oral(Rat) LD50; 2937 mg/kg ^[2]	Eye (rabbit): 6 mg - moderate
		Skin (rabbit): 500 mg/24h - mild
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

MARINE SHIELD UV SAIL FLEX PART A	Data demonstrate that during inhalation exposure,aromatic hydrocarbons undergo substantial partitioning into adipose tissues. Generally,linear and branched-chain alkyl esters are hydrolysed to their component alcohols and carboxylic acids in the intestinal tract, blood and most tissues throughout the body.
P-TOLUENESULFONYL ISOCYANATE	for p-toluenesulfonyl isocyanate The acute oral toxicity (LD50) of PTSI is 2600 mg/kg. for p-toluenesulfonamide (PTSA): PTSA was studied for oral toxicity in rats in a single dose toxicity test at doses of 889, 1333, 2000 and 3000 mg/kg in females and 2000 mg/kg in males, and in an OECD combined repeat dose and reproductive/developmental toxicity screening test at doses of 0, 120, 300 and 750 mg/kg/day in both sexes .PTSA was also tested for mutagenicity with assays for reverse mutation in bacteria and chromosomal aberrations in cultured Chinese hamster (CHL) cells.
XYLENE	Reproductive effector in rats The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
ETHYLBENZENE	Liver changes, uterual tract, effects on fertility, foetotoxicity, specific developmental abnormalities (musculoskeletal system) recorded. Ethylbenzene is readily absorbed following inhalation, oral, and dermal exposures, distributed throughout the body, and excreted primarily through urine. NOTE: Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA. WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.
NAPHTHA PETROLEUM, LIGHT, HYDROTREATED	For Low Boiling Point Naphthas (LBPNS): Acute toxicity: LBPNS generally have low acute toxicity by the oral (median lethal dose [LD50] in rats > 2000 mg/kg-bw), inhalation (LD50 in rats > 5000 mg/m3) and dermal (LD50 in rabbits > 2000 mg/kg-bw) routes of exposure Most LBPNS are mild to moderate eye and skin irritants in rabbits, with the exception of heavy catalytic cracked and heavy catalytic reformed naphthas, which have higher primary skin irritation indices. Sensitisation: LBPNS do not appear to be skin sensitizers, but a poor response in the positive control was also noted in these studies Repeat dose toxicity: The lowest-observed-adverse-effect concentration (LOAEC) and lowest-observed-adverse-effect level (LOAEL) values identified following short-term (2-89 days) and subchronic (greater than 90 days) exposure to the LBPNS substances. The High Benzene Naphthas (HBNs; Lower Olefins and Aromatics -LOA - CAT H) Category was developed for the HPV Program by grouping ethylene manufacturing streams (products) that exhibit commonalities from both manufacturing process and compositional perspectives. for petroleum: Altered mental state, drowsiness, peripheral motor neuropathy, irreversible brain damage (so-called Petrol Sniffer's Encephalopathy), delirium, seizures, and sudden death have been reported from repeated overexposure to some hydrocarbon solvents, naphthas, and gasoline This product may contain benzene which is known to cause acute myeloid leukaemia and n-hexane which has been shown to metabolize to compounds which are neuropathic. This product contains toluene. DHC Solvent Chemie (for EC No.: 926-605-8)

MARINE SHIELD UV SAIL FLEX PART A

DIETHYLENE GLYCOL DIBENZOATE	The U.S. EPA High Production Volume Information System (HPVIS 2009) lists both diethylene glycol dibenzoate (DEGDB) and dipropylene glycol dibenzoate (DPGDB) as non-mutagenic and non-carcinogenic.
PROPYLENE GLYCOL MONOMETHYL ETHER - MIXTURE OF ISOMERS	NOTE: Exposure of pregnant rats and rabbits to the substance did not give rise to teratogenic effects at concentrations up to 3000 ppm.
ETHYL-3-ETHOXYPROPIONATE	* Union Carbide ** Endura Manufacturing
HEXAMETHYLENE DIISOCYANATE	for diisocyanates: In general, there appears to be little or no difference between aromatic and aliphatic diisocyanates as toxicants. for 1,6-hexamethylene diisocyanate: Exposures to HDI are often associated with exposures to its prepolymers, especially to a trimeric biuretic prepolymer of HDI (HDI-BT), which is widely used as a hardener in automobile and airplane paints, and which typically contains 0.5-1% unreacted HDI.
HEXAMETHYLENE DIISOCYANATE POLYMER	* Bayer SDS ** Ardex SDS The material may produce moderate eye irritation leading to inflammation.
ETHYLENE GLYCOL PHENYL ETHER	Bacterial cell mutagen The aryl alkyl alcohol (AAA) fragrance ingredients are a diverse group of chemical structures with similar metabolic and toxicity profiles. The AAA fragrances demonstrate low acute and subchronic dermal and oral toxicity. At concentrations likely to be encountered by consumers, AAA fragrance ingredients are non-irritating to the skin. The potential for eye irritation is minimal. With the exception of benzyl alcohol and to a lesser extent phenethyl and 2-phenoxyethyl AAA alcohols, human sensitization studies, diagnostic patch tests and human induction studies, indicate that AAA fragrance ingredients generally have no or low sensitization potential.
MARINE SHIELD UV SAIL FLEX PART A & P-TOLUENESULFONYL ISOCYANATE & HEXAMETHYLENE DIISOCYANATE & HEXAMETHYLENE DIISOCYANATE POLYMER	Allergic reactions which develop in the respiratory passages as bronchial asthma or rhinoconjunctivitis, are mostly the result of reactions of the allergen with specific antibodies of the IgE class and belong in their reaction rates to the manifestation of the immediate type. Particular attention is drawn to so-called atopic diathesis which is characterised by an increased susceptibility to allergic rhinitis, allergic bronchial asthma and atopic eczema (neurodermatitis) which is associated with increased IgE synthesis. Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Isocyanate vapours/mists are irritating to the upper respiratory tract and lungs; the response may be severe enough to produce bronchitis with wheezing, gasping and severe distress, even sudden loss of consciousness, and pulmonary oedema.
MARINE SHIELD UV SAIL FLEX PART A & HEXAMETHYLENE DIISOCYANATE & HEXAMETHYLENE DIISOCYANATE POLYMER	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema.
MARINE SHIELD UV SAIL FLEX PART A & PROPYLENE GLYCOL MONOMETHYL ETHER - MIXTURE OF ISOMERS	for propylene glycol ethers (PGEs): Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM). Testing of a wide variety of propylene glycol ethers Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series.
P-TOLUENESULFONYL ISOCYANATE & PROPYLENE GLYCOL MONOMETHYL ETHER - MIXTURE OF ISOMERS & HEXAMETHYLENE DIISOCYANATE	Asthma-like symptoms may continue for months or even years after exposure to the material ceases.
XYLENE & ETHYLBENZENE & ETHYLENE GLYCOL PHENYL ETHER	The material may produce severe irritation to the eye causing pronounced inflammation.
XYLENE & ETHYLBENZENE & DIETHYLENE GLYCOL DIBENZOATE & PROPYLENE GLYCOL MONOMETHYL ETHER - MIXTURE OF ISOMERS & ETHYL-3-ETHOXYPROPIONATE & HEXAMETHYLENE DIISOCYANATE POLYMER & ETHYLENE GLYCOL PHENYL ETHER	The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).
NAPHTHA, PETROLEUM, HYDRODESULFURISED HEAVY & PROPYLENE GLYCOL MONOMETHYL ETHER - MIXTURE OF ISOMERS & HEXAMETHYLENE DIISOCYANATE & HEXAMETHYLENE DIISOCYANATE POLYMER	No significant acute toxicological data identified in literature search.
NAPHTHA, PETROLEUM, HYDRODESULFURISED HEAVY & NAPHTHA PETROLEUM, LIGHT, HYDROTREATED	Studies indicate that normal, branched and cyclic paraffins are absorbed from the mammalian gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30.
DIETHYLENE GLYCOL DIBENZOATE & PROPYLENE GLYCOL MONOMETHYL ETHER - MIXTURE OF ISOMERS	The material may be irritating to the eye, with prolonged contact causing inflammation.

MARINE SHIELD UV SAIL FLEX PART A

Acute Toxicity	✗	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	✓
Serious Eye Damage/Irritation	✗	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✓
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

MARINE SHIELD UV SAIL FLEX PART A	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available

p-toluenesulfonyl isocyanate	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	72h	Algae or other aquatic plants	10mg/l	2
	EC50	72h	Algae or other aquatic plants	25mg/l	2
	LC50	96h	Fish	>45mg/l	2
	EC50	48h	Crustacea	>100mg/l	2

xylene	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	4.6mg/l	2
	LC50	96h	Fish	2.6mg/l	2
	EC50	48h	Crustacea	1.8mg/l	2
ethylbenzene	NOEC(ECx)	73h	Algae or other aquatic plants	0.44mg/l	2

ethylbenzene	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	4.6mg/l	1
	LC50	96h	Fish	3.381-4.075mg/L	4
	EC50	48h	Crustacea	1.37-4.4mg/l	4
	NOEC(ECx)	720h	Fish	0.381mg/L	4
naphtha, petroleum, hydrodesulfurised heavy	EC50	96h	Algae or other aquatic plants	3.6mg/l	2

naphtha, petroleum, hydrodesulfurised heavy	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	72h	Algae or other aquatic plants	0.1mg/l	1
	EC50	72h	Algae or other aquatic plants	13mg/l	1
	EC50(ECx)	96h	Algae or other aquatic plants	64mg/l	2
	EC50	96h	Algae or other aquatic plants	64mg/l	2
	NOEC(ECx)	504h	Crustacea	0.097mg/l	2
	EC50	72h	Algae or other aquatic plants	0.53mg/l	2
	EC50	96h	Algae or other aquatic plants	0.58mg/l	2
	EC50(ECx)	48h	Crustacea	>100mg/l	1
	EC50	48h	Crustacea	>100mg/l	1
	EC50	96h	Algae or other aquatic plants	450mg/l	1
	NOEC(ECx)	72h	Algae or other aquatic plants	<0.1mg/l	1
	EC50	72h	Algae or other aquatic plants	6.5mg/l	1
	LC50	96h	Fish	>100000mg/L	4
	EC50	96h	Algae or other aquatic plants	64mg/l	2
	EC50(ECx)	24h	Crustacea	36mg/l	1
	LC50	96h	Fish	0.628mg/L	4
	NOEC(ECx)	72h	Algae or other aquatic plants	<0.1mg/l	1
	EC50	72h	Algae or other aquatic plants	6.5mg/l	1
	LC50	96h	Fish	8.8mg/l	4
	EC50	96h	Algae or other aquatic plants	64mg/l	2
	NOEC(ECx)	72h	Algae or other aquatic plants	<0.1mg/l	1
	EC50	72h	Algae or other aquatic plants	6.5mg/l	1
	EC50	96h	Algae or other aquatic plants	64mg/l	2

Continued...

MARINE SHIELD UV SAIL FLEX PART A

	NOEC(ECx)	720h	Crustacea	0.024mg/l	2
	LC50	96h	Fish	0.14mg/l	2
	EC50	96h	Algae or other aquatic plants	0.277mg/l	2
naphtha petroleum, light, hydrotreated	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	504h	Crustacea	0.17mg/l	2
	LC50	96h	Fish	4.26mg/l	2
	EC50	48h	Crustacea	0.64mg/l	2
	EC50	96h	Algae or other aquatic plants	64mg/l	2
diethylene glycol dibenzoate	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
propylene glycol monomethyl ether - mixture of isomers	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>1000mg/l	2
	LC50	96h	Fish	>100mg/l	2
	EC50	48h	Crustacea	373mg/l	2
	NOEC(ECx)	336h	Fish	47.5mg/l	2
	EC50	96h	Algae or other aquatic plants	>1000mg/l	2
ethyl-3-ethoxypropionate	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	48h	Crustacea	970mg/l	1
	EC50	72h	Algae or other aquatic plants	>114.86mg/l	2
	LC50	96h	Fish	45.3mg/l	2
	EC50	48h	Crustacea	970mg/l	1
hexamethylene diisocyanate	Endpoint	Test Duration (hr)	Species	Value	Source
	EC0(ECx)	24h	Crustacea	<0.33mg/l	1
	EC50	72h	Algae or other aquatic plants	>77.4mg/l	2
	LC50	96h	Fish	22mg/l	1
hexamethylene diisocyanate polymer	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>1000mg/l	2
	LC50	96h	Fish	8.9mg/l	2
	NOEC(ECx)	72h	Algae or other aquatic plants	50mg/l	2
ethylene glycol phenyl ether	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>100mg/l	2
	LC50	96h	Fish	154mg/l	2
	EC50	48h	Crustacea	460mg/l	2
	NOEC(ECx)	24h	Fish	5mg/l	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark.

For aromatic hydrocarbons:

Within an aromatic series, acute toxicity increases with increasing alkyl substitution on the aromatic nucleus.

for polyisocyanates:

Polyisocyanates are not readily biodegradable.

For n-heptane:

log Kow : 4.66

Koc : 2400-8100

Half-life (hr) air : 52.8

Half-life (hr) H2O surface water : 2.9-312

Henry's atm m3 /mol: 2.06

BOD 5 if unstated: 1.92

COD : 0.06

BCF : 340-2000

log BCF : 2.53-3.31

Environmental fate:

Photolysis or hydrolysis of n-heptane are not expected to be important environmental fate processes.

Continued...

MARINE SHIELD UV SAIL FLEX PART A

Hydrolysis would represent the primary fate mechanism for the majority of the commercial isocyanate monomers, but, is tempered somewhat by the lack of water solubility.

For xylenes :

log Koc : 2.05-3.08

Koc : 25.4-204

Half-life (hr) air : 0.24-42

Half-life (hr) H₂O surface water : 24-672

Half-life (hr) H₂O ground : 336-8640

Half-life (hr) soil : 52-672

Henry's Pa m³/mol: 637-879

Henry's atm m³/mol: 7.68E-03

BOD 5 if unstated: 1.4,1%

COD : 2.56,13%

ThOD : 3.125

BCF : 23

log BCF : 1.17-2.41

Environmental Fate

Terrestrial fate: Measured Koc values of 166 and 182, indicate that 3-xylene is expected to have moderate mobility in soil.

for UV filters:

UV filters have been detected in surface water, wastewater and fish, and some of them are estrogenic in fish.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
p-toluenesulfonyl isocyanate	HIGH	HIGH
xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)
ethylbenzene	HIGH (Half-life = 228 days)	LOW (Half-life = 3.57 days)
diethylene glycol dibenzoate	LOW	LOW
propylene glycol monomethyl ether - mixture of isomers	LOW (Half-life = 56 days)	LOW (Half-life = 1.7 days)
ethyl-3-ethoxypropionate	LOW	LOW
hexamethylene diisocyanate	LOW	LOW
hexamethylene diisocyanate polymer	HIGH	HIGH
ethylene glycol phenyl ether	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
p-toluenesulfonyl isocyanate	LOW (LogKOW = 2.3424)
xylene	MEDIUM (BCF = 740)
ethylbenzene	LOW (BCF = 79.43)
diethylene glycol dibenzoate	LOW (LogKOW = 3.0406)
propylene glycol monomethyl ether - mixture of isomers	LOW (BCF = 2)
ethyl-3-ethoxypropionate	LOW (LogKOW = 1.0809)
hexamethylene diisocyanate	LOW (LogKOW = 3.1956)
hexamethylene diisocyanate polymer	LOW (LogKOW = 7.5795)
ethylene glycol phenyl ether	LOW (LogKOW = 1.16)

Mobility in soil

Ingredient	Mobility
p-toluenesulfonyl isocyanate	LOW (KOC = 882.1)
ethylbenzene	LOW (KOC = 517.8)
diethylene glycol dibenzoate	LOW (KOC = 542.3)
propylene glycol monomethyl ether - mixture of isomers	HIGH (KOC = 1)
ethyl-3-ethoxypropionate	LOW (KOC = 10)
hexamethylene diisocyanate	LOW (KOC = 5864)
hexamethylene diisocyanate polymer	LOW (KOC = 18560000)
ethylene glycol phenyl ether	LOW (KOC = 12.12)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	► Containers may still present a chemical hazard/ danger when empty. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. ► DO NOT allow wash water from cleaning or process equipment to enter drains. ► Recycle wherever possible.
------------------------------	---

Continued...

MARINE SHIELD UV SAIL FLEX PART A

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	NO
HAZCHEM	*3Y

Land transport (UN)

UN number	1263				
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)				
Transport hazard class(es)	<table> <tr> <td>Class</td><td>3</td></tr> <tr> <td>Subrisk</td><td>Not Applicable</td></tr> </table>	Class	3	Subrisk	Not Applicable
Class	3				
Subrisk	Not Applicable				
Packing group	III				
Environmental hazard	Not Applicable				
Special precautions for user	<table> <tr> <td>Special provisions</td><td>163; 223; 367</td></tr> <tr> <td>Limited quantity</td><td>5 L</td></tr> </table>	Special provisions	163; 223; 367	Limited quantity	5 L
Special provisions	163; 223; 367				
Limited quantity	5 L				

Air transport (ICAO-IATA / DGR)

UN number	1263														
UN proper shipping name	Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)														
Transport hazard class(es)	<table> <tr> <td>ICAO/IATA Class</td><td>3</td></tr> <tr> <td>ICAO / IATA Subrisk</td><td>Not Applicable</td></tr> <tr> <td>ERG Code</td><td>3L</td></tr> </table>	ICAO/IATA Class	3	ICAO / IATA Subrisk	Not Applicable	ERG Code	3L								
ICAO/IATA Class	3														
ICAO / IATA Subrisk	Not Applicable														
ERG Code	3L														
Packing group	III														
Environmental hazard	Not Applicable														
Special precautions for user	<table> <tr> <td>Special provisions</td><td>A3 A72 A192</td></tr> <tr> <td>Cargo Only Packing Instructions</td><td>366</td></tr> <tr> <td>Cargo Only Maximum Qty / Pack</td><td>220 L</td></tr> <tr> <td>Passenger and Cargo Packing Instructions</td><td>355</td></tr> <tr> <td>Passenger and Cargo Maximum Qty / Pack</td><td>60 L</td></tr> <tr> <td>Passenger and Cargo Limited Quantity Packing Instructions</td><td>Y344</td></tr> <tr> <td>Passenger and Cargo Limited Maximum Qty / Pack</td><td>10 L</td></tr> </table>	Special provisions	A3 A72 A192	Cargo Only Packing Instructions	366	Cargo Only Maximum Qty / Pack	220 L	Passenger and Cargo Packing Instructions	355	Passenger and Cargo Maximum Qty / Pack	60 L	Passenger and Cargo Limited Quantity Packing Instructions	Y344	Passenger and Cargo Limited Maximum Qty / Pack	10 L
Special provisions	A3 A72 A192														
Cargo Only Packing Instructions	366														
Cargo Only Maximum Qty / Pack	220 L														
Passenger and Cargo Packing Instructions	355														
Passenger and Cargo Maximum Qty / Pack	60 L														
Passenger and Cargo Limited Quantity Packing Instructions	Y344														
Passenger and Cargo Limited Maximum Qty / Pack	10 L														

Sea transport (IMDG-Code / GGVSee)

UN number	1263						
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)						
Transport hazard class(es)	<table> <tr> <td>IMDG Class</td><td>3</td></tr> <tr> <td>IMDG Subrisk</td><td>Not Applicable</td></tr> </table>	IMDG Class	3	IMDG Subrisk	Not Applicable		
IMDG Class	3						
IMDG Subrisk	Not Applicable						
Packing group	III						
Environmental hazard	Not Applicable						
Special precautions for user	<table> <tr> <td>EMS Number</td><td>F-E , S-E</td></tr> <tr> <td>Special provisions</td><td>163 223 367 955</td></tr> <tr> <td>Limited Quantities</td><td>5 L</td></tr> </table>	EMS Number	F-E , S-E	Special provisions	163 223 367 955	Limited Quantities	5 L
EMS Number	F-E , S-E						
Special provisions	163 223 367 955						
Limited Quantities	5 L						

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Continued...

MARINE SHIELD UV SAIL FLEX PART A

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002669	Surface Coatings and Colourants Flammable Carcinogenic Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

p-toluenesulfonyl isocyanate is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

xylene is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

ethylbenzene is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

naphtha, petroleum, hydrosulfurised heavy is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

naphtha petroleum, light, hydrotreated is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

New Zealand Inventory of Chemicals (NZIoC)

diethylene glycol dibenzoate is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

propylene glycol monomethyl ether - mixture of isomers is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

ethyl-3-ethoxypropionate is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

hexamethylene diisocyanate is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

hexamethylene diisocyanate polymer is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

ethylene glycol phenyl ether is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Approved Hazardous Substances with controls	New Zealand Inventory of Chemicals (NZIoC)
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals	

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
3.1C	500 L in containers more than 5 L	250 L
3.1C	1 500 L in containers up to and including 5 L	250 L

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
6.5A or 6.5B	120	1	3	
3.1C or 3.1D				10 L

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (p-toluenesulfonyl isocyanate; xylene; benzotriazol derivatives; ethylbenzene; naphtha, petroleum, hydrodesulfurised heavy; naphtha petroleum, light, hydrotreated; diethylene glycol dibenzoate; ethyl-3-ethoxypropionate; hexamethylene diisocyanate; ethylene glycol phenyl ether)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (benzotriazol derivatives)
Japan - ENCS	No (benzotriazol derivatives; naphtha petroleum, light, hydrotreated; hexamethylene diisocyanate polymer)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (p-toluenesulfonyl isocyanate; benzotriazol derivatives; hexamethylene diisocyanate polymer)
Vietnam - NCI	Yes
Russia - FBEPH	No (benzotriazol derivatives)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	04/03/2025
Initial Date	06/09/2021

SDS Version Summary

Version	Date of Update	Sections Updated
1.3.7.11	04/03/2025	Company address, CAS number for Benzotriazol derivatives

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.
The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit

MARINE SHIELD UV SAIL FLEX PART A

IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit.
IDLH: Immediately Dangerous to Life or Health Concentrations
ES: Exposure Standard
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index
AIC: Australian Inventory of Industrial Chemicals
DSL: Domestic Substances List
NDSL: Non-Domestic Substances List
IECSC: Inventory of Existing Chemical Substance in China
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers
ENCS: Existing and New Chemical Substances Inventory
KECI: Korea Existing Chemicals Inventory
NZIoC: New Zealand Inventory of Chemicals
PICCS: Philippine Inventory of Chemicals and Chemical Substances
TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas
NCI: National Chemical Inventory
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.