



FOR MANUAL USE

# FIBER FILM™

## PS PRO HD

### Product Overview

**PS PRO HD** is a user-friendly, **pre-stretched stretch film with reinforced elements**. Designed for manual applications, it is ergonomically engineered to **unwind smoothly and stretch easily**, allowing users to wrap pallets faster and with less effort.

**PS PRO HD** offers an optimized **cling-to-slip balance**, making it **easier to find the film edge**, and **more forgiving in use** thanks to improved elasticity.

The **PS PRO series** delivers excellent performance, providing high holding force and superior load stability.

Technical Specifications		
		TOLERANCE
Film Width (mm)	420	2%
Net Roll Weight (g/roll)	1560	5%
Film Weight (g/m)	2.6	5%

Pallet dimensions: 80cm x 120cm x 205cm

Packaging Specifications	
Film Length per Roll* (m)	600
Core Diameter (mm)	51
Core Weight (kg)	0.205
Rolls per Box	6
Boxes per Pallet	56
Rolls per pallet	336
*Length Tolerance	±2%

#### Instructions for storage and use:

The film should be stored in closed, dry and dust-free rooms, storage temperature +5°C to +30°C with complementary conditions:

Protected against sunrays exposure and away from heat-emitting sources (heaters, radiators, hot air ventilators)

-The film should be protected against humidity and dust

-The film should be protected against mechanical damages

-The film should be stored on the pallets. Direct contact with concrete or floor is not allowed

Disclaimer: Data presented herein is based on internal tests. No liability, warranty or guarantee of product performance is created by this document. To improve our products, our company reserves the right to modify any of the technical specifications included here without giving any notice.



FOR MANUAL USE

**FIBER FILM™**  
**PS PRO GP**

## Product Overview

**PS PRO GP** is a user-friendly, **pre-stretched stretch film with reinforced elements**. Designed for manual applications, it is ergonomically engineered to **unwind smoothly and stretch easily**, allowing users to wrap pallets faster and with less effort.

**PS PRO GP** offers an optimized **cling-to-slip balance**, making it **easier to find the film edge**, and **more forgiving in use** thanks to improved elasticity.

The **PS PRO series** delivers excellent performance, providing high holding force and superior load stability.

Technical Specifications		
Film Width (mm)	420	TOLERANCE 2%
Net Roll Weight (g/roll)	1330	5%
Film Weight (g/m)	2.2	5%

Pallet dimensions: 80cm x 120cm x 205cm

Packaging Specifications	
Film Length per Roll* (m)	600
Core Diameter (mm)	51
Core Weight (kg)	0.205
Rolls per Box	6
Boxes per Pallet	64
Rolls per pallet	384
*Length Tolerance	±2%

### Instructions for storage and use:

The film should be stored in closed, dry and dust-free rooms, storage temperature +5°C to +30°C with complementary conditions:

Protected against sunrays exposure and away from heat-emitting sources (heaters, radiators, hot air ventilators)

-The film should be protected against humidity and dust

-The film should be protected against mechanical damages

-The film should be stored on the pallets. Direct contact with concrete or floor is not allowed

Disclaimer: Data presented herein is based on internal tests. No liability, warranty or guarantee of product performance is created by this document. To improve our products, our company reserves the right to modify any of the technical specifications included here without giving any notice.



FOR MANUAL USE

## Product Overview

**PS PRO L** is a user-friendly, **pre-stretched stretch film with reinforced elements**. Designed for manual applications, it is ergonomically engineered to **unwind smoothly and stretch easily**, allowing users to wrap pallets faster and with less effort.

**PS PRO L** offers an optimized **cling-to-slip balance**, making it **easier to find the film edge**, and **more forgiving in use** thanks to improved elasticity.

The **PS PRO series** delivers excellent performance, providing high holding force and superior load stability.

Technical Specifications		
Film Width (mm)	420	TOLERANCE 2%
Net Roll Weight (g/roll)	1200	5%
Film Weight (g/m)	2.0	5%

Pallet dimensions: 80cm x 120cm x 205cm

Packaging Specifications	
Film Length per Roll* (m)	600
Core Diameter (mm)	51
Core Weight (kg)	0.205
Rolls per Box	6
Boxes per Pallet	64
Rolls per pallet	384
*Length Tolerance	±2%

### Instructions for storage and use:

The film should be stored in closed, dry and dust-free rooms, storage temperature +5°C to +30°C with complementary conditions:

Protected against sunrays exposure and away from heat-emitting sources (heaters, radiators, hot air ventilators)

-The film should be protected against humidity and dust

-The film should be protected against mechanical damages

-The film should be stored on the pallets. Direct contact with concrete or floor is not allowed

Disclaimer: Data presented herein is based on internal tests. No liability, warranty or guarantee of product performance is created by this document. To improve our products, our company reserves the right to modify any of the technical specifications included here without giving any notice.