



FOR MACHINE USE

FIBER FILM™
PS PRO HD

Product Overview

PS PRO HD is a **pre-stretched stretch film with reinforced elements**, designed for machine applications.

It is ergonomically engineered to provide an **optimized cling-to-slip balance** and **slightly increased elasticity**, ensuring an efficient pallet wrapping process.

PS PRO HD delivers excellent performance, offering **high holding force, strong tear resistance, and superior load stability**.

With its optimized design and lower weight, **PS PRO series reduces palletization costs** compared to the average pre-stretched stretch films available on the market.

Technical Specifications		
Film Width (mm)	420	TOLERANCE 2%
Net Roll Weight (g/roll)	7800	5%
Film Weight (g/m)	2.6	5%

Pallet dimensions: 80cm x 120cm x 205cm

Packaging Specifications	
Film Length per Roll* (m)	3000
Core Diameter (mm)	77
Core Weight (kg)	0.930
Rolls per pallet	36
*Length Tolerance	±2%

Instructions for storage and use:

The film should be stored in closed, dry and dust-free rooms, storage temperature +5°C to +30°C with complementary conditions:

Protected against sunrays exposure and away from heat-emitting sources (heaters, radiators, hot air ventilators)

- The film should be protected against humidity and dust
- The film should be protected against mechanical damages
- The film should be stored on the pallets. Direct contact with concrete or floor is not allowed

Disclaimer: Data presented herein is based on internal tests. No liability, warranty or guarantee of product performance is created by this document. To improve our products, our company reserves the right to modify any of the technical specifications included here without giving any notice.



FOR MACHINE USE

Product Overview

PS PRO GP is a **pre-stretched stretch film with reinforced elements**, designed for machine applications.

It is ergonomically engineered to provide an **optimized cling-to-slip balance** and **slightly increased elasticity**, ensuring an efficient pallet wrapping process.

PS PRO GP delivers excellent performance, offering **high holding force, strong tear resistance, and superior load stability**.

With its optimized design and lower weight, **PS PRO series reduces palletization costs** compared to the average pre-stretched stretch films available on the market.

Technical Specifications		
Film Width (mm)	420	TOLERANCE 2%
Net Roll Weight (g/roll)	6660	5%
Film Weight (g/m)	2.2	5%

Pallet dimensions: 80cm x 120cm x 205cm

Packaging Specifications	
Film Length per Roll* (m)	3000
Core Diameter (mm)	77
Core Weight (kg)	0.930
Rolls per pallet	36
*Length Tolerance	±2%

Instructions for storage and use:

The film should be stored in closed, dry and dust-free rooms, storage temperature +5°C to +30°C with complementary conditions:

Protected against sunrays exposure and away from heat-emitting sources (heaters, radiators, hot air ventilators)

- The film should be protected against humidity and dust
- The film should be protected against mechanical damages
- The film should be stored on the pallets. Direct contact with concrete or floor is not allowed

Disclaimer: Data presented herein is based on internal tests. No liability, warranty or guarantee of product performance is created by this document. To improve our products, our company reserves the right to modify any of the technical specifications included here without giving any notice.



FOR MACHINE USE

FIBER FILM™
PS PRO L

Product Overview

PS PRO L is a **pre-stretched stretch film with reinforced elements**, designed for machine applications.

It is ergonomically engineered to provide an **optimized cling-to-slip balance** and **slightly increased elasticity**, ensuring an efficient pallet wrapping process.

PS PRO L delivers excellent performance, **offering high holding force, strong tear resistance, and superior load stability.**

With its optimized design and lower weight, **PS PRO series reduces palletization costs** compared to the average pre-stretched stretch films available on the market.

Technical Specifications		
Film Width (mm)	420	TOLERANCE 2%
Net Roll Weight (g/roll)	6000	5%
Film Weight (g/m)	2.0	5%

Pallet dimensions: 80cm x 120cm x 205cm

Packaging Specifications	
Film Length per Roll* (m)	3000
Core Diameter (mm)	77
Core Weight (kg)	0.930
Rolls per pallet	36
*Length Tolerance	±2%

Instructions for storage and use:

The film should be stored in closed, dry and dust-free rooms, storage temperature +5°C to +30°C with complementary conditions:

Protected against sunrays exposure and away from heat-emitting sources (heaters, radiators, hot air ventilators)

- The film should be protected against humidity and dust
- The film should be protected against mechanical damages
- The film should be stored on the pallets. Direct contact with concrete or floor is not allowed

Disclaimer: Data presented herein is based on internal tests. No liability, warranty or guarantee of product performance is created by this document. To improve our products, our company reserves the right to modify any of the technical specifications included here without giving any notice.