

# SNTPT6436LPZZ

Thermal & Optical Bi-spectrum Stable PTZ Camera



## Key Features

- VOx uncooled focal plane detector with 640×512 resolution
- NETD ≤ 40mK
- 26 to 105mm motorized thermal lens optical, 37x optical zoom module
- Support human/vehicle detection
- Support smoke & fire detection and fire point detection
- Smart events: intrusion, single line crossing, double line crossing, loitering, wrong-way, people counting, enter area, leave area
- Support 3 temperature measurement rule types (spot, line, area)
- Temperature measurement range: -20°C to 150°C (-4°F to 302°F)
- Power off self-locking, strong wind resistance
- Anti-frozen, IP66

## Specification

Thermal Module	
Image Sensor	Uncooled VOx Focal Plane Arrays
Resolution	Sensor is 640×512. Image can be scaled up to 1280×1024
Pixel Pitch	12μm
NETD	≤ 40mK
Spectral Range	8 to 14 μm
Image Setting	Brightness, Sharpness, Contrast, Mirror, FFC control, 2D/3D DNR
Pseudo-color Setting	White-hot/Black-hot/Rainbow/Ironbow etc. up to 17 modes
Thermal Lens	
Focus Control	Motorized Focus
Focal Length	26 to 105mm
Aperture	F1.6
Angle of View	H: 16.8° to 4.2°, V: 13.4° to 3.4°
Detection Distance (Fire: 1×1m)	Max 4,375m (14,353.7ft)
Detection Distance (Human: 1.8×0.5m)	Max 4,369m (14,334.0ft)
Detection Distance (Vehicle: 4×1.5m)	Max 10,063m (33,015.1ft)
Recognition Distance (Human: 1.8×0.5m)	Max 1,192m (3,910.8ft)
Recognition Distance (Vehicle: 4×1.5m)	Max 3,659m (12,004.6ft)
Note: The detection ranges are calculated with Johnson's criteria and vary in different weather conditions. *Product performance is based on testing in a controlled environment. Your results may vary due to several external and environmental factors.	
Optical Module	
Image Sensor	1/1.8" CMOS
Max. Resolution	2592 (H)×1520 (V), 4MP
Shutter Speed	1/5 to 1/20,000s
Min. Illumination	Color: 0.001 Lux @ (F1.5, AGC ON), B/W: 0.0001 Lux (F1.5, AGC ON),, 0 Lux with light
WDR	True WDR
Focal Length	6.8 to 251 mm, 37x optical zoom
Aperture	F1.5 to F4.8
Angle of View	H: 60.7° to 2.33°, V: 36.8° to 1.38°
Digital Zoom	16x
Focus Control	Auto/Manual/Semi-automatic
Mirror	Support

Defog	Support
Privacy Masking	Support
<b>PTZ</b>	
Pan/Tilt Range	Pan: 0° to 360° endless, Tilt: +90° to -90°
Pan/Tilt Speed	Pan: 0.01° to 60°/s, Tilt: 0.01° to 30°/s
Wiper	Support
Preset Accuracy	± 0.1°
Presets	400
Scan	8 scans
Patrol	12 patrols, up to 32 presets per patrol
Track	6 tracks
3D Positioning	Support
Speed Setup	Auto/Manual (0-8)
Power Off Memory	Support
Idle Motion	The time can be set (1-240 minutes), and functions such as preset positions, patrols, scans, and tracks can be run.
<b>Illuminator</b>	
Illuminator Type	Laser
Illumination Distance	Up to 500m (1,640.4ft)
<b>Video and Audio</b>	
Main Stream	Thermal: 1280×1024, 1280×720, 640×512 @ 25/30fps Optical: 2592×1520, 2560×1440, 2304×1296, 1920×1080, 1280×720 @25/30fps
Sub Stream	Thermal: D1, CIF @ 25/30fps Optical: D1, VGA @25/30fps
Bit Rate Control	CBR/VBR
Bit Rate	Thermal: Main stream: 100Kbps to 8Mbps Sub stream: 100Kbps to 6Mbps Optical: Main stream: 100Kbps to 16Mbps, Sub stream: 100Kbps to 6Mbps
Region of Interest	Off/On (8 Zone, Rectangle)
Audio Compression	G711: 64kbps, RAW_PCM: 128kbps
<b>Smart Function</b>	
Smart Alarm	Motion detection, Disk alarm, I/O alarm, IVS alarm, Temperature detection & alarm
Smart Detection	Support human/vehicle detection, fire point detection and smoke & fire detection (ship detection optional)
Intelligent Analysis	Intrusion, Single line crossing, Double line crossing, Loitering, Wrong-way, Enter area, Leave area (these 7 function support accurate detection of people/vehicles), People counting
<b>Temperature Detection</b>	
Temperature Detection	3 temperature measurement rule types, 20 rules in total, 1 full screen, 19 others (spot, areas, line).
Temperature Alarm	Over temperature alarm, Temperature difference alarm
Accuracy	±2°C / ±2%

Response Time	≤ 30ms
Temperature Range	-20°C to 150°C (-4°F to 302°F)
<b>Network</b>	
Protocols	IPv4/IPv6 ,HTTP,RTSP/RTP/RTCP, TCP/UDP, DHCP, DNS, PPPOE, SMTP, 802.1x
Interoperability	ONVIF, CGI, SDK
Max. User Access	10 Users
Web Viewer	<IE11, Chrome, Firefox, Microsoft Edge
Web Language	English, Chinese, Polish, Italian, Portuguese, Spanish. Russian, French, Czech, Hungarian
<b>Interface</b>	
Network Interface	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio Interface	2ch Audio In, 2ch Audio Out
Alarm Interface	9ch Alarm In, 4ch Alarm Out
RS485	Support
BNC Output	Support
Reset Button	Support (Built-in)
SD Card Slot	Built-in, up to 256GB
<b>General</b>	
Power Supply	DC36V
Power Consumption	Max 150W
Working Temperature	-40°C to 60°C (-40°F to 140°F)
Storage Conditions	0 to 90% RH
Certifications	CE /FCC
Ingress Protection	IP66
Casing	Metal
Dimensions	594×350×337mm (23.39×13.78×13.27")
Net Weight	≤ 26.6Kg (58.6lb)
<b>Ordering Information</b>	
<b>Model</b>	<b>Description</b>
SN-TPT6436LPZ-Z4-ZSD37	Thermal Focal Length: 26 to 105mm Optical Focal Length: 6.8 to 251 mm, 37x optical zoom

Dimensions (mm)

