

Electronic Pressure Heat Assist Cold Laminator

LaMounter-1700M

The LaMounter-1700M is a new heat-assisted cold laminator featuring electronic nip pressure control, ensuring precise application of pressure for every lamination. Designed for optimal performance and consistency, it guarantees superior results with every use.

PRODUCT OVERVIEW



FEATURES

- Electronic nip pressure control
- High Grade Silicone Rollers for Consistent Lamination
- Rear Slitters for Inline Print Separation
- Maximum Speed of Just Over 49 ft/min
- Foot Pedal & Rear Remote Included
- Integrated Rear Material Rewinder
- Shaft Bar Roll Media Centering Guides
- Adjustable roller gap to 1 inch

SPECIFICATIONS

Description	LaMounter-1700M
Power Consumption	1600 W
Max laminating width	1520 mm
Film thickness	25 – 500 mic (1 – 20 mil)
Max laminating speed	16 m/min
No backing paper-film	Yes
Max temperature control	40 °C / 60 °C
Mounting thickness	25 mm
Film core size	3" Auto grip
Foot S/W	Yes
Safety system	Laser system
Roller diameter	Ø 130 mm
Max film diameter	Ø 150 mm
Unit dimensions (W x D x H)	2090 x 655 x 1250 mm
Carton dimensions (W x D x H)	2185 x 746 x 775 mm
Carton weight	190 kg