MAX ONE TX3300 MFP

Scan, Copy, Print and Edit

A Professional MFP solution for companies requiring a versatile digital workflow



SCAN, COPY, ENHANCE AND SAVE YOUR ORIGINALS IN ONE SINGLE FLOW


The MAX ONE36 TX3300 MFP is easy to set up and use, yet incredibly flexible, with options such as WiFi, an internal controller and intuitive touchscreen. With the touchscreen, you can mark-up, copy, share and collaborate.


The solution for small workgroups, companies and organizations who enjoy a modern work environment – and fewer trips to the copy shop. The MAX ONE36 TX3300 MFP is a professional solution for scanning, editing, sharing and printing.


FEATURES:

- 36” Scan, Print and Copy
- TX Stacker
- Scan To Copy, File, USB, Email And Cloud
- Easy To Use Touch Tablet
- Live Preview with Markups
- Black And White Point Adjustment
- Closed Loop Calibration For Perfect Copies
- Built in controller, no PC required
- Lucia Pro II Pigment Ink


Scan to USB


Scan to Copy


Scan to File


Scan to Cloud


Markup and Edit

Drafting Clinic Canada Limited
Wide Format Imaging Solutions

1500 Trinity Drive, Mississauga, Ontario L5T 1L6 Phone: 800.567.3222 Email: sales@dccltd.ca Web: www.dccltd.ca

Scanner Specifications

Maximum Scan Width	36" (914 mm)
Maximum Media Width	38" (965 mm)
Weight & Dimensions	12.3kg (27.1 lbs) 1163 x 227 x 125mm
Touch Panel / Screen	7" Multi Touch Screen

Scan speed (inch/sec) colour and monochrome while scanning 24" document

150 dpi	300 dpi	600 dpi
3.8	1.9	1.0

Optical Resolution	600 dpi
Maximum Resolution	9600 dpi
Scanning Technology	Contex CleanScan
Scan to USB	Yes 3.0
Maximum Media Thickness	0.03" / 0.75mm
Accuracy	0.1% +/- 1 pixel
Data Capture (colour/mono)	48-bit
Colour Space	sRGB (24 bit) / Grayscale (8 bit) / Monochrome (1 bit)
Connectivity	Ethernet
Energy Star Compliant	Yes
Operating Software	Windows 10, 8, 7 and Vista, 64-bit
Power Consumption	Ready 26, Power Save 3.6, Scanning 31W, ENERGY STAR© Certified
Power Requirements	External power supply 100-240V, 60/50Hz, 33W
Whats in the box	Scanner, 2 m Ethernet cable, external power supply, installation guide, calibration poster, calibration sheet and cleaning cloth.

Printer Specifications

Printer Type	5-Colour 36-inch Printer
Number of Nozzles	Total: Total: 15,360 MBK:5,120 nozzles - C,M,Y,BK:2,560 each
Print Resolution	2400 x1200 dpi (Max)
Line Accuracy	±0.1% or Less
Ink Droplet Size	5 picoliter
Ink Type	Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)
Ink Tank	Shipped with Printer: 160ml C/Y/M/BK; 330ml MBK **Replacement:** MBK: PFI-113 (160ml)/PFI-313 (330ml)/PFI-713 (700ml) M: PFI-111 (160ml)/PFI-311 (330ml)/PFI-711 (700ml) BK/C/Y: PFI-110 (160ml)/PFI-310 (330ml)/PFI-710 (700ml)
Standard Memory	128 MB (Virtual) 2 GB (Physical)
Hard Drive	256 GB
Media Width	Cut Sheet: 8" - 36", Roll Feed: 10" - 36"
Media Thickness	0.07-0.8mm (2.8-31.4mil)
Maximum Roll Print Length	Roll Feed: 59' (18 meters)
Maximum Media Roll Diameter	6.7" (150mm)
Paper Feed Method	Roll Feed: One Roll, front output
Front Loading Manual Feed:	One sheet, front output
Operating System	Windows 7, 8.1, 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit), MacOS v10.15.7- MacOS 14
Print Language	SGRaster, HP-GL/2, HP RTL, PDF, JPEG, CALS G4
Standard Interfaces	USB B Port: Hi-Speed USB (12 Mbit/sec, 480 Mbit/sec) USB A Port: USB drive Gigabit Ethernet: IEEE 802.3u/ab/x (100/1000Base-T, Full Duplex), SNMP, HTTP, TCP/IP (IPv4/IPv6), FTP Wi-Fi: IEEE 802.11n/g/b
Noise Level Approx	Operation Approx: 51 dB (A) Standby Approx: 35 dB (A) Acoustic Power: Approx 6.9 Bels
Power Consumption	Maximum: Approx. 83 W Standby: Approx. 1.7 W Power Off: Approx. 0.1 W
Power Source	AC-100-240V (50-60Hz)
Printer Dimensions (W x D x H) and Weight	With Basket Open: 54.7" x 41.1" x 46"; 242.5 lbs. With Basket Closed: 54.7" x 30.2" x 46"; 242.5 lbs. With Stacker Opened: 54.7" x 46.8" x 46"; 253.5 lbs. With Stacker Closed: 54.7" x 44.2" x 46"; 253.5. lbs.
Printer Package Dimensions (W x D x H) and Weight	Printer (Main Unit with Stand and Pallet): 62.9" x 35.5" x 44.2"; 352.7 lbs. Basket: 52" x 34" x 241.4"; 59.5 lbs. Stacker: 49.2" x 35.7" x 11.5"; 57.3 lbs. Roll Unit: 60" x 22.1" x 18.1"; 66.1 lbs.
Operating Environment	Temperature: 59°-86° F (15°-30° C) Relative Humidity - 10-80% (No Condensation)
Options	• Multifunction Roll System (RU-34) • 2"/3" Roll Holder Set (RH2-34) User-Replaceable Items • Ink Tank (PFI-110/111/113, PFI-310/311/313, PFI-710/711/713) • Printhead (PF-06) • Maintenance Cartridge (MC-30) • Cutter Blade (CT-07)

Drafting Clinic Canada Limited
Wide Format Imaging Solutions
1500 Trinity Drive, Mississauga, Ontario L5T 1L6 Phone: 800.567.3222 Email: sales@dccltd.ca Web: www.dccltd.ca