# MAX ONE44 TX4300 MFP

## Scan, Copy, Print and Edit

**A Professional MFP solution for companies requiring a versatile digital workflow**




## SCAN, COPY, ENHANCE AND SAVE YOUR ORIGINALS IN ONE SINGLE FLOW


The MAX ONE44 TX4300 MFP is easy to set up and use, yet incredibly flexible, with options such as WiFi, an internal controller and intuitive touchscreen. With the touchscreen, you can mark-up, copy, share and collaborate.


The solution for small workgroups, companies and organizations who enjoy a modern work environment – and fewer trips to the copy shop. The MAX ONE44 TX4300 MFP is a professional solution for scanning, editing, sharing and printing.


### FEATURES:

- 44” Scan, Print and Copy
- TX Stacker
- Scan To Copy, File, USB, Email And Cloud
- Easy To Use Touch Tablet
- Live Preview with Markups
- Black And White Point Adjustment
- Closed Loop Calibration For Perfect Copies
- Built in controller, no PC required
- Lucia Pro II Pigment Ink


Scan to USB


Scan to Copy


Scan to File


Scan to Cloud


Markup and Edit

**Drafting Clinic Canada Limited**
*Wide Format Imaging Solutions*

1500 Trinity Drive, Mississauga, Ontario L5T 1L6 Phone: 800.567.3222 Email: sales@dccltd.ca Web: www.dccltd.ca

## Scanner Specifications

| | |
|---|---|
| Maximum Scan Width | 44" (1118mm) |
| Maximum Media Width | 47.2" (1200 mm) |
| Weight & Dimensions | 14.1kg (31 lbs) 1349x227x125mm |
| Touch Panel / Screen | 7" Multi Touch Screen |

Scan speed (inch/sec) colour and monochrome while scanning 24" document

| 150 dpi | 300 dpi | 600 dpi |
|---|---|---|
| 3.8 | 1.9 | 1.0 |

| | |
|---|---|
| Optical Resolution | 600 dpi |
| Maximum Resolution | 9600 dpi |
| Scanning Technology | Contex CleanScan |
| Scan to USB | Yes 3.0 |
| Maximum Media Thickness | 0.03" / 0.75mm |
| Accuracy | 0.1% +/- 1 pixel |
| Data Capture (colour/mono) | 48-bit |
| Colour Space | sRGB (24 bit) / Grayscale (8 bit) / Monochrome (1 bit) |
| Connectivity | Ethernet |
| Energy Star Compliant | Yes |
| Operating Software | Windows 10, 8, 7 and Vista, 64-bit |
| Power Consumption | Ready 26, Power Save 3.6, Scanning 31W, ENERGY STAR© Certified |
| Power Requirements | External power supply 100-240V, 60/50Hz, 33W |
| Whats in the box | Scanner, 2 m Ethernet cable, external power supply, installation guide, calibration poster, calibration sheet and cleaning cloth. |

## Printer Specifications

| | |
|---|---|
| Printer Type | 5-Colour 36-inch Printer |
| Number of Nozzles | Total: Total: 15,360 MBK:5,120 nozzles - C,M,Y,BK:2,560 each |
| Print Resolution | 2400 x1200 dpi (Max) |
| Line Accuracy | ±0.1% or Less |
| Ink Droplet Size | 5 picoliter |
| Ink Type | Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK) |
| Ink Tank | **Shipped with Printer:**<br>330ml MBK/BK/C/Y/M<br>**Replacement:**<br>MBK: PFI-113 (160ml)/PFI-313 (330ml)/PFI-713 (700ml)<br>M: PFI-111 (160ml)/PFI-311 (330ml)/PFI-711 (700ml)<br>BK/C/Y: PFI-110 (160ml)/PFI-310 (330ml)/PFI-710 (700ml) |
| Standard Memory | 128 MB (Virtual) 2 GB (Physical) |
| Hard Drive | 256 GB |
| Media Width | Cut Sheet: 6" - 44", Roll Feed: 6" - 44" |
| Media Thickness | 0.07-0.8mm (2.8-31.4mil) |
| Maximum Roll Print Length | Roll Feed: 59' (18 meters) |
| Maximum Media Roll Diameter | 6.7" (150mm) |
| Paper Feed Method | Roll Feed: One Roll, front output |
| Front Loading Manual Feed: | One sheet, front output |
| Operating System | Windows 7, 8.1, 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit), MacOS v10.15.7- MacOS 14 |
| Print Language | SGRaster, HP-GL/2, HP RTL, PDF, JPEG, CALS G4 |
| Standard Interfaces | USB B Port: Hi-Speed USB (12 Mbit/sec, 480 Mbit/sec)<br>USB A Port: USB drive<br>Gigabit Ethernet: IEEE 802.3u/ab/x (100/1000Base-T, Full Duplex), SNMP, HTTP, TCP/IP (IPv4/IPv6), FTP<br>Wi-Fi: IEEE 802.11n/g/b |
| Noise Level Approx | Operation Approx: 51 dB (A)<br>Standby Approx: 35 dB (A)<br>Acoustic Power: Approx 6.9 Bels |
| Power Consumption | Maximum: Approx. 84 W<br>Standby: Approx. 1.7 W<br>Power Off: Approx. 0.1 W |
| Power Source | AC-100-240V (50-60Hz) |
| Printer Dimensions (W x D x H) and Weight | With Basket Open: 62.7" x 41.1" x 46.0"; 260.1 lbs.<br>With Basket Closed: 62.7" x 30.2" x 46.0" 260.1 lbs.<br>With Stacker Opened: 62.7" x 46.8" x 46.0"; 273.4 lbs.<br>With Stacker Closed: 62.7" x 44.2" x 46.0"; 273.4 lbs. |
| Printer Package Dimensions (W x D x H) and Weight | Printer (Main Unit with Stand and Pallet):<br>70.9" x 35.5" x 44.8"; 381.4 lbs.<br>Basket: 60.0" x 34.0" x 24.1"; 66.1 lbs.<br>Stacker: 57.6" x 35.7" x 11.5"; 64 lbs.<br>Roll Unit: 68.0" x 22.1" x 18.1"; 72.8 lbs. |
| Operating Environment | Temperature: 59°-86° F (15°-30° C)<br>Relative Humidity - 10-80% (No Condensation) |
| Options | • Multifunction Roll System RU-44<br>• 2"/3" Roll Holder Set RH2-46<br>**User-Replaceable Items**<br>• Ink Tank (PFI-110/111/113, PFI-310/311/313, PFI-710/711/713)<br>• Printhead (PF-06)<br>• Maintenance Cartridge (MC-30)<br>• Cutter Blade (CT-07) |

**Drafting Clinic Canada Limited**
*Wide Format Imaging Solutions*
1500 Trinity Drive, Mississauga, Ontario L5T 1L6 Phone: 800.567.3222 Email: sales@dccltd.ca Web: www.dccltd.ca