NSC CEILING/WALL-MOUNTED SPEAKERS, EN 54-24

PART NUMBER	PRODUCT DESCRIPTION
S61165-00	**NSC wall-mounted loudspeaker WM 6-165 EN54**

- Impact-resistant housing; ceramic block and thermal fuse 6 watts; IP54 rating; EN 54-24; 1438-CPR-1040

- The 6W speaker is equipped with a 165mm full-range speaker chassis and a 100V transformer with 3 power adjustments.
- The high-density, impact-resistant MDF enclosure in white enables a low-resonance sound.
- A robust perforated sheet steel grille cover ensures continuous stability.
- Additional operational safety is provided by the integrated 2-pole ceramic block and thermal fuse, as well as the moisture impregnation of the speaker chassis.
- The speaker is also protected against the risks of environmental influences with a high IP 54 rating.
- The speaker also conforms to British Standard BS 5839, Part 8.
- The proven spring clamp on the rear panel ensures quick wall mounting.

Power	6/3/1,5 W
Impedance (100V)	1667/3333/6667 ohm
Pmax @20kHz (100V)	1,71 W
Frequency Range	197 - 21.900 Hz
Frequency Response	172 - 23.500 Hz
SPL 1W/1m, peak	100,6 dB
SPL 1W/4m, peak	88,6 dB
SPL Pmax/4m, peak	96,3 dB
SPL IEC268-5, 1W/1m	93,0 dB
SPL EN54-24, Pmax/4m	90,0 dB
Sensitivity EN54-24, 1W/1m	93,0 dB
Sensitivity EN 54-24, 1W/4m	81,0 dB
Dispersion -6dB, 500Hz	h=180° v=180°
Dispersion -6dB, 1KHz	h=160° v=160°
Dispersion -6dB, 2KHz	h=125° v=125°
Dispersion -6dB, 4KHz	h=89° v=89°
IP Rating	IP54
Type A/B	A (Indoor)
Temperature Range	-10°C to +55 C°
Connector	2-pin ceramic block
Clamp diameter	3,2 mm
Maximum cable entry	8 mm²
Dimensions	253 x 194 x 82 mm
Weight (net)	1,95 kg
Color	White
Mounting	Spring clamp