

Metal Silicone 2* Sealant

Product Description

Metal Silicone 2 sealant is 100% waterproof and ideal for sealing metal substrates and weatherproofing. This high performance and durable sealant offers a fast cure and can be exposed to rain or water in as little as 30 minutes. Metal Silicone 2 sealant is permanently flexible, shrink-proof, and crack-proof. It offers strong adhesion to metal substrates and will not blemish most metal finishes. It can be applied to either wet or dry surfaces, is sun-proof and freeze-proof, and will not breakdown or wash away. Backed by a lifetime guarantee.

Product Attributes

- Fast cure: 30-minute tack free and 24-hour full cure⁽¹⁾
- 30-minutes rain and water exposure⁽¹⁾
- 100% weatherproof, freeze-proof and sun-proof, will not degrade in harsh climates
- Meets ASTM C-920 Class 25 specifications
- Permanently flexible to keep gaps sealed, shrink-proof and crack-proof
- Will never break down due to extreme weather conditions
- Resist mold⁽²⁾ with 10-year mold-free product protection
- Excellent adhesion for wet or dry applications⁽³⁾
- Will not blemish high-end metal finishes such as chrome, bronze and nickel
- Neutral curing sealant adheres to more surfaces including most metals, aluminum, and stainless steel
- Freeze/thaw stability
- Non-paintable



(1) 30-minute tack free time, 24-hour full cure and exposure to rain or water possible in as little as 30 minutes with bead size max 3/16", temperature min 65°F and humidity min 50%. Otherwise, sealant should not be exposed to water for 8 hours. Do not touch or clean caulk for 24 hours

(2) Cured sealant is resistant to stain-causing mold & mildew. Regular cleaning of sealant is required, however, as soap and other residue can cause secondary mold and mildew growth

(3) For wet surface application, wipe off excess water before applying

* Silicone 2 is a trademark of Momentive Performance Materials Inc.