



RULES FOR EXITING AN ELEVATED LIFT

1. Leaving the basket of an elevated lift is ONLY allowed when either or both of the following scenarios are realized;
 - a. There are no other means to access the area that needs to be accessed
 - b. Other means of access would create a greater hazard to the worker(s)
2. Inspect all fall protection equipment daily for any signs of defect or damage. If found to be defective or damaged red tag and remove from service.
3. A ground person MUST be present at all times if a free climb is to take place.
4. Inspect lift anchorage points for defect or damage. If found to be defective or damaged, red tag and remove from service.
5. 100% tie-off at all times per MIOSHA Part 45 Fall Protection.
6. Exit out of gates only.
7. When making a temporary anchorage attachment to structural steel, the only thing that you can have in your hands is the temporary anchorage device.
 - When the temporary anchorage point is established, return to the lift and retrieve a second retractable device and hang it from the anchorage point.
 - Attach the second retractable device to the full body harness and return to lift. Remove retractable device that is anchored to the lift and at that point get any tools and material needed to complete the job.
 - When removing the temporary anchorage device and second retractable device, you must be tied off to the anchorage devices in the lift.
8. If you are unable to find an approved anchorage point outside of the lift you may remain tied off to the approved anchorage point in the lift. This is allowed only when all other options outside the aerial lift have been exhausted.

Dedicated People. Delivering Quality.