





Pro Range Levelling Devices



GANTERUD L5 Pro

Levelling and turning when lifting

- Auto levelling
- Load capacity: Max. 5 tons
- Load imbalance capacity: Max. 750 kg
- Unloaded weight: 139 kg
- Standard chain length: 3 meters
- Release of chain wheel with remote control
- Flash light warning when chain wheel is released.
- Auto levelling, finds the center of gravity automatically when chain wheel is released.
- Snatch block function with released chain wheel.



GANTERUD L12 Pro

Levelling and turning when lifting

- Auto levelling
- Load capacity: Max. 12 tons
- Load imbalance capacity: Max. 2500 kg
- Unloaded weight: 295 kg
- Standard chain length: 4 meters
- Release of chain wheel with remote control
- Flash light warning when chain wheel is released.
- Auto levelling, finds the center of gravity automatically when chain wheel is released.
- Snatch block function with released chain wheel.



GANTERUD L20-3 Pro

Levelling and turning when lifting

- Auto levelling
- Load capacity: Max. 20 tons
- Load imbalance capacity: Max. 3 tons
- Unloaded weight: 395 kg
- Standard chain length: 6 meters
- Release of chain wheel with remote control
- Flash light warning when chain wheel is released.
- Auto levelling, finds the center of gravity automatically when chain wheel is released.
- Snatch block function with released chain wheel.



**Easy to use. The remote control
has a range of up to 100 meters.**

Other than cleaning, the only thing you need to think about is charging the battery. The battery status is indicated on the levelling device and, with normal use, it is sufficient to charge the battery once a week.

Proven and robust technology in a new application

Basic Range Levelling Devices



GANTERUD L3

Levelling and turning when lifting

- Load capacity: Max. 3 tons
- Load imbalance capacity: Max. 500 kg
- Unloaded weight: 126 kg
- Standard chain length: 3 meters



GANTERUD L5

Levelling and turning when lifting

- Load capacity: Max. 5 tons
- Load imbalance capacity: Max. 750 kg
- Unloaded weight: 139 kg
- Standard chain length: 3 meters

Heavy Duty Range Levelling Devices



GANTERUD L10 Heavy Duty

Levelling and turning when lifting

- Load capacity: Max. 10 tons
- Load imbalance capacity: Max. 4 tons
- Unloaded weight: 180 kg
- Standard chain length: 3 meters



GANTERUD L50 Heavy Duty

Levelling and turning when lifting

- Load capacity: Max. 50 tons
- Load imbalance capacity: Max. 10 tons
- Unloaded weight: 1150 kg
- Standard chain length: 6 meters



Lift Safer

Safely level your units with our levelling solutions. We ensure stability by finding the equilibrium. Control everything with a remote and minimize the risk of damage to both personnel and load!



Lift Faster

Revolutionize your assembly process with Ganterud's levelling devices and save up to 25% of your assembly time!



Lift Greener

Reduce CO2 emissions by up to 50% with our environmentally conscious solution. Make a significant impact on your carbon footprint by choosing our innovative technology.



GANTERUD
Lifting Solutions

Ganterud Lifting Solutions AB
Frögatan 10
SE 653 36 Karlstad
Sweden

Find your dealer: ganterud.se



Scan for video clips!