



# GANTERUD

Lifting Solutions





## Pro Series Levelling Devices



### GANTERUD L5 Pro

Levelling and turning  
when lifting

- Auto levelling
- Load capacity: Max. 5 tons
- Load imbalance capacity: Max. 750 kg
- Unloaded weight: 139 kg
- Standard chain length: 3 meters
- Release of chain wheel with remote control.
- Flash light warning when chain wheel is released.
- Auto levelling, finds the center of gravity automatically when chain wheel is released.
- Snatch block function with released chain wheel.



### GANTERUD L5 Pro plus

Upcoming model  
Levelling and turning  
when lifting

- Memory function
- Auto levelling
- Load capacity: Max. 5 tons
- Load imbalance capacity: Max. 750 kg
- Unloaded weight: 139 kg
- Standard chain length: 3 meters
- Release of chain wheel with remote control.
- Flash light warning when chain wheel is released.
- Auto levelling, finds the center of gravity automatically when chain wheel is released.
- Snatch block function with released chain wheel.



### GANTERUD L12 Pro

Levelling and turning  
when lifting

- Auto levelling
- Load capacity: Max. 12 tons
- Load imbalance capacity: Max. 2500 kg
- Unloaded weight: 295 kg
- Standard chain length: 4 meters
- Release of chain wheel with remote control.
- Flash light warning when chain wheel is released.
- Auto levelling, finds the center of gravity automatically when chain wheel is released.
- Snatch block function with released chain wheel.



### GANTERUD L20-3 Pro

Levelling and turning  
when lifting

- Auto levelling
- Load capacity: Max. 20 tons
- Load imbalance capacity: Max. 3 tons
- Unloaded weight: 395 kg
- Standard chain length: 6 meters
- Release of chain wheel with remote control.
- Flash light warning when chain wheel is released.
- Auto levelling, finds the center of gravity automatically when chain wheel is released.
- Snatch block function with released chain wheel.

# Proven and robust technology in a new application

## Heavy Duty Series Levelling Devices



### GANTERUD L10 Heavy Duty

Levelling and turning  
when lifting

- Load capacity: Max. 10 tons
- Load imbalance capacity: Max. 4 tons
- Unloaded weight: 260 kg
- Standard chain length: 3 meters



### GANTERUD L50 Heavy Duty

Upcoming model, sales start Q2  
Levelling and turning  
when lifting

- Load capacity: Max. 50 tons
- Load imbalance capacity: Max. 15 tons
- Unloaded weight: 1150 kg
- Standard chain length: 6 meters

## Basic Series Levelling Devices



### GANTERUD L3

Levelling and turning  
when lifting

- Load capacity: Max. 3 tons
- Load imbalance capacity: Max. 500 kg
- Unloaded weight: 126 kg
- Standard chain length: 3 meters

The only maintenance required, aside from cleaning, is charging the battery. The battery status is indicated on the levelling device and, with normal use, it is sufficient to charge the battery once a week.



**New!**  
Now even safer with  
emergency stop function!

### Easy to use

The remote control  
has a range of up to  
100 meters.

## Lift Safer

Safely level your units with our levelling solutions. We ensure stability by finding the equilibrium. Control everything with a remote and minimize the risk of damage to both personnel and load!

## Lift Faster

Revolutionize your assembly process with Ganterud's levelling devices and save up to 25% of your assembly time!

## Lift Greener

Reduce CO2 emissions by up to 50% with our environmentally conscious solution. Make a significant impact on your carbon footprint by choosing our innovative technology.

