



- The compact body allows for superior maneuverability in narrow spaces for parking.
- City driving range of 259km (WLTP)
- Fast charging (30 min SOC 30% to 80%)
- Max gradient 27%, IP67 Waterproof: Conquering every challenging terrain

### Compact body, versatile capacity

With a 2.5m³ super-large space, the G50 Piccolo easily accommodates more cargo, making your trips more efficient and cost-saving.





30 kW Peak Power Motor: Quick Acceleration, Powerful Performance



Powered by CATL batteries: delivering high quality, safety, and stability



Efficient Fast Charge + Home Slow Charge: Dual charging ports with dual temperature control protection























#### ANTI COLLISION BRAKE ASSIST OR AEB ASSIST

System reduces impact and enhances safety by automatically engaging brakes in potential front or rear collisions.



#### LANE DEPARTURE ALERT

accidents.

Utilizes the camera-based Lane Departure Warning to receive alerts when your vehicle unintentionally drifts out of the lane.



#### **OBSTACLE WARNING ALERT (Front And Rear)**

Obstacle detection sensors emit audible alerts with variable intervals, indicating the distance between the vehicle and obstacles. To reduce driver misoperation, firm pressing of the accelerate pedal is required to start the vehicle.




#### **MOVE OFF ALERT**

At traffic light or crawling traffic, audible alert activates when front vehicfe move forward by more than 4 meters.




#### **HILL START ASSIST**

During hill start, the vehicle prevents backward movement for approximately 5 seconds upon reapplication of the pedal, even if the brake is released.



#### **AUTO PARK GEAR ASSIST**

When the driver exits the vehicle in "D" or "R" gear, the system automatically switches to "P" gear to prevent unintended movement. This system prevents self-moving accidents.



## SMARTER POWER. CLEANER TOMORROW. MAXIMIZE SAVINGS TODAY!

The electric Linxys Piccolo is conceived in line with the principles of a sustainable and eco-friendly future.

The almost silent electric motor gives you a serene and relaxed driving experience, while boosting your bottom line through reducing your cost of operations.

	Linxys Piccolo	Diesel Van	Petrol Van
Average Daily Mileage	212 km	212 km	212 km
Energy Consumption per 212 km	30 kWh	16.5L	21.4L
Fuel per Unit (AC Charging)(*)	S\$0.55/ kWh	S\$2.64/L	S\$2.86/L
Fuel per Unit (DC Charging)(*)	S\$0.60/kWh	S\$2.64/L	S\$2.86/L
Fuel cost per 212 km (50% AC/ 50% DC)	S\$17.25	S\$36.81	S\$51.79
Annual Cost (365 days)	S\$6, 296.25	S\$13, 435.65	S\$22, 339.46










SPECIFICATIONS		G50 piccolo			
Overall dimensions (mm)		3395 x 1475 x 1950			
Dimensions	Container Volume (m³)	2.5			
	Wheelbase (mm)	2430			
Weight (kg)	GVWR	1480			
	Curb Weight	1130			
	Carry Payload	350			
Power Parameters	Driving Range (km)	259 (City)   166 (Combined)			
	Maximum Speed (km/h)	100			
Battery	Battery Type	Lithium Iron Phosphate (CATL)			
	Battery Capacity (kWh)	30			
	Fast Charging Time	30 min (SOC 30% - 80%)			
	Total Voltage (V)	320			
Driving	Max Power (kW)	30			
Motor	Max Torque (N·m)	120			
	Tread (mm)	1300 (Front)   1290 (Rear)			
Maneuverability .	Front/rear Overhang (mm)	130			
	Maximum Gradability (%)	26.7°			
	Maximum Turning Radius (m)	4.4			
	Tire Specifications	145/80 R12PR			
Chassis	Front Suspension	Macpherson independent suspension			
&	Rear Suspension	Multi-link non-independent suspension			
Braking System	Drive Axle	Rear Wheel Drive			
-,	Brake System	Front disc & rear drum hydraulic brakes			
	Driver Airbag	Standard			
	Passenger Airbag	Standard			
	Seat belt Reminder Alert	Standard			
	Anti-lock Braking System (ABS)	Standard			
Safety	Electronic Stability Control (ESC)	Standard			
Configuration	Autonomous Emergency Braking Assist	Standard			
	Lane Departure Warning	Standard			
	Move off Alert	Standard			
	Auto Park Gear Assist	Standard			
	Obstacle Warning Alert	Standard			
	Hill start Assist	Standard			
Other -	Electronic Brakeforce Distribution (EBD)	Standard			
	Seating Capacity	2			
	Detachable Table	Standard			
	Front UV protection glass	Standard			
	On-board Telematics	Standard			
	Reverse Camera/Reverse Sensor	Standard			
	Power Adjustable wing mirror	Standard			
	Keyless Entry & one-touch start system	Standard			
	Tyre Pressure Monitoring System	Standard			
	Charging Standard	CCS2 (AC + DC)			
BOOK	BOOK A TEST DRIVE WITH OUR SOLE AUTHORIZED DEALER TODAY!				

# piccolo







Rear Wheel Tread 1290



Please note: changes may have been made to the product since the editorial deadline. The manufacturer reserves the right to make changes to the design, form, colour and the product specification during the delivery period, provided these changes, while taking into account the interests of the vendor, can be deemed reasonable with respect to the purchaser. Where the seller or the manufacturer uses symbols or numbers to describe an order or the subject of an order, no rights may be derived solely from these. The illustrations may show accessories and items of optional equipment which are not part of standard specification.