

**ADVANCED RANGE
OF LIGHT INDUSTRIAL COATINGS**

Date: January 2026

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

QD Enamel



SECTION 1

IDENTIFICATION OF THE SUBSTANCE/PREPURATION

Name: QD Gloss Enamel
NO LEAD PIGMENTS PRESENT
CAS no. : N/A
UN No. : 1263
Kemler : 33

EC Label : N/A
EAC : 127
SAPMA : 2-H-E

EcoChem : 95.65.00
HazChem : 3[Y]E

SECTION 2:

COMPOSITION/INFORMATION ON INGREDIENTS

[F R11][Xn R20][R33][,N R50/53]
EC Classification : F Xn, N R11,20,33,50/53 S02,13,16,43A,46,51,56,59

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS
XYLENE >20%

[CAS #: 1330-20-7] [E.C. #: 601-022-00-9]

EEC Labels : XN OEL 435mg OEL 100ppm STOEL 650mg STOEL 150ppm RL+ S
>12.5%

[CAS #: 108-88-3] [E.C. #: 601-021-00-3]

EEC Labels : F XN OEL 188mg OEL 50ppm STOEL 560mg STOEL 150ppm RL+ S
<10%

[CAS #: 64742-88-7] [E.C. #: 649-405-00-X]

EEC Labels : XN OEL 575mg OEL 100ppm STOEL 720mg STOEL 125ppm RL

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

SECTION 3:

HAZARDS IDENTIFICATION

SAPMA Health Rating: 2-MODERATE - Temporary or minor injury possible even if treatment given

Inhalation: Irritating, narcotic. Can affect CNS.

Skin: Irritating, risk of dermatitis. May be absorbed.

Eyes: Irritating.

Ingestion: Irritating and nauseating.

No carcinogenic, mutagenic or genetic effects established

May have short term environmental effects. Contain, monitor & remove.

SECTION 4:

FIRST AID MEASURES

Inhalation: Move to fresh air. In case of discomfort seek medical attention.

Skin: Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention.

Eyes: Rinse immediately with plenty of water. Seek medical advice if symptoms persist.

Ingestion: Wash mouth with plenty of water. Do NOT induce vomiting. seek medical attention.

SECTION 5:

FIRE FIGHTING MEASURES

Flammable with toxic fumes. Potential for spontaneous combustion.

Containers can burst in a fire. Can form explosive vapour/air mixture. Static discharge hazard!

Foam. CO2. Dry powder. Fog to cool and control. Do NOT use water jets.

Cool containers in case of fire.

SECTION 6:

ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Contain & Collect. Use inert NOT sawdust. Remove waste to safe place - potential for spontaneous combustion.

SECTION 7:

HANDLING AND STORAGE

Store separately from any reactive substances - oxidisers in particular.

No open flames. No smoking.

Keep containers cool. Avoid free fall of liquid - use earthing.

Subject to local bylaws

SECTION 8:

EXPOSURE CONTROLS/PERSONAL PROTECTION

SAPMA Rating: 2-H-E PPE : Respirator and Eye protection

Inhalation: In case of insufficient ventilation, use suitable respiratory protection.

**ADVANCED RANGE
OF LIGHT INDUSTRIAL COATINGS**

Date: January 2026

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

QD Enamel.../continued (page 2)

Skin: Use barrier cream and impervious gloves.
 Eyes: Use face shield & goggles or full face respirator/hood. Avoid direct contact.
 Ingestion: Observe the rules of hygiene. Wash before eating, drinking or smoking.
 OEL Type : MIX- Mixture - See Section 2 Skin



SECTION 9:

PHYSICAL AND CHEMICAL PROPERTIES

Chemical class:	PAINT PRODUCT
Description:	VISCOUS LIQUID
Smell:	PUNGENT
Visc.:	+/- 75KU
SG:	>1.0
pH:	N/A
NV:	>50
FlashPoint (°C):	<23
Water:	Insoluble
Oil:	Miscible

SECTION 10:

STABILITY AND REACTIVITY

Stable under normal conditions
 Could generate static - USE EARTHING
 Potential for spontaneous combustion
 Inert - no reaction with fire-fighting water

SECTION 11:

TOXICOLOGICAL INFORMATION

No carcinogenic, mutagenic or genetic effects established
 Toxicity levels not established

SECTION 12:

ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove.

SECTION 13:

DISPOSAL INFORMATION

Use reputable waste contractors - potential for spontaneous combustion. Care with used containers.

SECTION 14:

TRANSPORT INFORMATION

UN No.:	1263 : PAINT PRODUCT NOS	Contains BUTANOLS and PAINT PRODUCT
Packing group:	II	IMO Class : 3.2
EAC:	127	
Hazchem:	3[Y]E	
Kemler:	33	



SECTION 15:

REGULATORY INFORMATION

EC no.:	n/a
Contains:	XYLENE, TOLUENE
EC Classification:	F Xn, N R11, 20, 33, 50/53 S02, 13, 16, 43A, 46, 51, 56, 59
R11:	Highly Flammable
R20:	Harmful by inhalation
R33:	Danger of cumulative effects
R50/53:	Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.
S2:	Keep out of reach of children. (Retail sales items)
S13:	Keep away from food, drink and animal feeding stuffs
S16:	Keep away from sources of ignition - No smoking

**ADVANCED RANGE
OF LIGHT INDUSTRIAL COATINGS**

Date: January 2026

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

QD Enamel.../continued (page 3)

S43A:
S46:
S51:
S56:
S59:

In case of fire, use water fog, foam or powder - Do not use water jets!
If swallowed seek medical advice immediately and show this container or label
Use only in well ventilated areas
Do not discharge into drains or the environment, dispose to an authorised waste collection point
Refer to manufacturer/supplier for information on recovery/recycling



SECTION 16: OTHER INFORMATION

Take precautionary measures against static discharges.
In case of any discomfort always seek medical advice.

This MSDS conforms with General Administrative Regulations of 6 Sept.1996 (ISO-11014/ANSI Z400.1.1996)
OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug. 1995 (EH-42)
SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)
All information is given in good faith but without guarantee in respect of accuracy.
No responsibility is accepted for errors or omissions or the consequences thereof.
These recommendations were extracted from the EcoChem database (Les Fisher - 031-2660523).