**COMMERCIAL RIBBED** CS20, CS24, CS26 **RELIABLE** QUALITY **PERFORMANCE M**IDLAND<sup>™</sup>

#### **COLORS**









\*Printed colors may not be accurate. Contact your local Midland dealer for exact color samples

White

Sandtone

SPECIFICATIONS	CS20	CS24	CS26
Plain Steel U-Factor	Unrated	Unrated	Unrated
<b>U-Factor</b> R-Value: T-Bond:	<b>0.38</b> 7.05	<b>0.38</b> 7.05	<b>0.38</b> <sub>7.05</sub>
Thickness	2 inches	2 inches	2 inches
Maximum Width	40 ft 2 in	24 ft 2 in	16 ft 2 in
Exterior Steel	20 gauge	24 gauge	26 gauge
Warranty* Excludes Springs	10 years	10 years	25 years
*For full warranty details contact your Midland dealer *ColorSelect™ uses Sherwin Williams Polane® Solar Reflective Polyurethane Enamel, providing a durable, heat-repelling coating.			

## **GLASS**





Satin\* Low E



Obscure



Double Dark\*



Gray

### **WINDOWS**





24" x 12"

#### TRACK MOUNTING



Reverse Angle Mounted Track Continuous leg-in angle to attach to steel jambs



#### Angle Mounted Track Continuous leg-out angle used on larger doors to attach to wood jambs

## **PACKAGE UPGRADES**

Heavy-Duty Hardware Package available

# TRACK CONFIGURATIONS



installations



roof



Vertical Lift To put horizontal Full vertical track as close to rise where ceiling as possible headroom is available





<sup>\*</sup>Tempered only.