**COMMERCIAL** 

# THERMOGUARD<sup>TM</sup>

UNCOMPROMISING QUALITY AND STRENGTH



### **COLORS**













2-Inch ThermoGuard™

\*Printed colors may not be accurate. Contact your local Midland dealer for exact color samples

#### **SPECIFICATIONS** 3-Inch ThermoGuard™

<b>U-Factor</b> R-Value	<b>0.11</b>	0.14
Foam/Insulate	Polyurethane	Polyurethane
Thickness	3 inches	2 inches
Maximum Width	40 ft. 2 In.	32 ft. 2 in.
Exterior Steel	27 gauge 20 gauge upgrade, white only	27 gauge 20 gauge upgrade, white only
Interior Steel	27 gauge	27 gauge
Warranty* Excludes Springs	10 years	10 years
*For full warranty details contact your Midland dealer	The state of	100
*ColorSelect™ uses Sherwin		

# **WINDOWS**







\*Only available in 3-inch

# TRACK MOUNTING




Reverse Angle Mounted Track Continuous leg-in angle to attach to steel jambs



## Angle Mounted Track Continuous leg-out angle used on larger doors to attach to wood jambs

# **GLASS**









\*Tempered only.



**PACKAGE UPGRADES** 

Heavy-Duty Hardware Package available

#### TRACK CONFIGURATIONS



Standard Lift For normal installations



**Inclined Track** To follow pitchof roof



Vertical Lift Full vertical track as close to rise where headroom is ceiling as possible available



