

CERAMIC COATING AFTERCARE GUIDE

PROTECT YOUR INVESTMENT. KEEP THAT SHOWROOM SHINE.



OFFICIAL CALIFORNIA
DETAILING



OWNER'S PRIDE


CURE PHASES AFTER INSTALLATION



3-4 HOURS

Water Resistance

After rain/condensation safe after this first phase.



7 DAYS

Chemical Resistance

Do NOT wash for minimum of 7 days.



30 DAYS

Full Cure

Full hardness, gloss, and chemical resistance performance achieved.



DO NOT DRY WIPE/DUST OFF VEHICLE.
DUST IS NOT HARMFUL FOR YOUR CAR



DO NOT HOSE OFF AND AIR DRY YOUR CAR
TO CLEAN IT "AVOIDING CHEMICALS"



One free outside wash 7-14 days after install
(you must schedule)

Included in Inspection Wash is a demonstration wash and "checkup" on the coating condition after install, answering any questions you may have.

DO'S




HAND WASH ONLY

Use OP Eco Wash Hand Washes or touchless car wash.



WASH EVERY 2-4 WEEKS

Keeps your coating performing at its best.



WASH FROM TOP DOWN

Leave the dirtiest sections for last to avoid cross contamination.



INSPECT REGULARLY

Coated surface advises inspection every 6-12 months.



KEEP IT CLEAN

Regular washing helps maintain gloss, slickness, and protection.



USE COATING-SAFE PRODUCTS

Use Ceramic+, Ceramic Detailer, or Slick - Owner's Pride Maintenance Products.

DON'TS



DO NOT WASH FOR 7 DAYS MINIMUM

Allow coating to fully cure.



DO NOT USE DRIVE-THRU CAR WASHES

Brushes, mitts, and recycled water can damage the coating.



DO NOT USE HARSH CHEMICALS OR CLEANERS

Avoid degreasers, bug/tar removers, or abrasive products.



DO NOT POLISH OR USE ABRASIVES

Polishing or abrasives will diminish coating depth or remove it entirely.



DO NOT AIR DRY OR LET WATER SPOT

Always dry to prevent hard water spots.



DO NOT DRY WIPE OR DUST OFF

This can swirl or scratch the coating.



WASHING / MAINTENANCE

- ✓ Use OP Eco Wash Hand Washes or touchless car wash.
- ✓ Wash every 2-4 weeks minimum.
- ✓ Wash from the top down.
- ✓ Avoid washing or drying in direct sunlight.
- ✓ Coated surface advises inspection every 6-12 months.
- ✓ Yearly chemical decontamination washes to remove contaminants and boost performance (not mandatory).



DRYING

- ✓ Always completely dry your coated surface.
- ✓ OP Ceramic+ Drying Aid and Plush Microfiber Drying Towel is recommended.
- ✓ Use a clean, soft drying towel and drying agents.
- ✓ Do not allow coated surface to "air dry" - forced air/dryers/blowers are helpful.
- ✗ **DO NOT HOSE OFF AND LET DRY.** San Diego's water is extremely hard and WILL water spot your car.



SPOT / CONTAMINATION REMOVAL

- ✗ Do not polish/scrub/aggressively agitate your coated surfaces.
- ✗ **DO NOT DRY WIPE, DUST OFF, CALIFORNIA DUSTER, WATERLESS WASH YOUR CAR. WILL SWIRL/MAR/SCRATCH YOUR COATED PAINT.**
- ✓ Do not use unapproved/aggressive products/chemicals to attempt to remove contaminations.
- ✓ Bird droppings, tar, sap, bugs, etc. should be removed from the coated surface as soon as possible.
- ✓ Temporary staining may occur from failure to remove contamination; it will wash away over time.
- ✓ Contact the installer for assistance or guidance with removal of contamination or spots.

PRO TIP

Regular maintenance is the key to long-lasting protection and an easier clean every time. Treat your coating like a high-performance product it is, and it will perform for years.



HOW TO WASH A COATED CAR VIDEO

Scan to watch our step-by-step guide for the safest way to wash and protect your coating.



SCAN ME



OFFICIAL CALIFORNIA
DETAILING

619-760-4962
San Diego, CA
OfficialCaliforniaDetailing.com

WARRANTY SUPPORT:
Contact OCD or Owner's Pride Warranty for any questions or assistance.



OWNER'S PRIDE