

M&S MR1 Cage 125mm Castor Specification

Version 1 Mar-2024

Marks & Spencer are ordering to the specifications laid out in this document and it is our expectation that all aspects will be met in full.

First off samples must be signed off prior to any collections / deliveries, following initial acceptance random samples will be taken during the delivery window and tested to ensure compliance to these specifications.

M&S reserve the right to refuse any products which do not comply with the following specification.

125 mm Castors are attached to the M&S Roll Cage.

Specification

Dimensions

Height:	154mm
Wheel Diameter:	125mm
Swivel Radius:	93mm Maximum
Hub Width:	48mm
Tyre Width:	35mm
Load Capacity:	250kg (Per Castor)
Fixing:	Rectangular Plate 105x85, 4 off holes on 80 / 77 x 60 Centres

Bearing Detail

Castor Swivel: 5/16" & 5mm steel balls in a double ball race
Wheel: Roller bearing

Material Detail

Top Plate:	Mild steel 4mm thick Zinc plated
Fork:	Mild steel 3.5mm thick Zinc plated
Wheel Hub & Tyre:	Polypropylene
Wheel Infill:	Thermoplastic Rubber
Thread guard:	Nylon
Lubrication:	Low Temperature Grease
Operating Temp:	-20 to 50°C

All Castors should be available for deliver on the UK mainland within 12 weeks of an official purchase order.