

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

SECTION 1: IDENTIFICATION

Product name : DIESEL TREATMENT CR - 300ML

Product code : 5861 006 300

Manufacturer or supplier's details

Company : Wurth Australia Pty. Ltd.

Address : Building 5, 43 - 63 Princes Highway
Dandenong South, VIC 3175

Telephone : +61 3 8788 1111

Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National
Poisons Centre: 131 126

E-mail address : product@wurth.com.au

Recommended use of the chemical and restrictions on use

Recommended use : Fuels and fuel additives

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 4

Serious eye damage/eye irritation : Category 2A

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H227 Combustible liquid.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
 Date of first issue: 03.04.2013

Supplemental Hazard Statements : AUH044 Risk of explosion if heated under confinement.
 AUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P264 Wash skin thoroughly after handling.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P331 Do NOT induce vomiting.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Vapours may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	>= 60 -<= 100
2-Ethylhexyl nitrate	27247-96-7	< 10
2-Ethylhexan-1-ol	104-76-7	< 10
(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	>= 1 -< 3
Morpholine	110-91-8	< 1

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.

DIESEL TREATMENT CR - 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 22.06.2024
13.0	09.10.2024	10781510-00018	Date of first issue: 03.04.2013

- If inhaled : When symptoms persist or in all cases of doubt seek medical advice.
: If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water
for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control centre immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes serious eye irritation.
Repeated exposure may cause skin dryness or cracking.
- Protection of first-aiders : First Aid responders should pay attention to self-protection,
and use the recommended personal protective equipment
when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Hazchem Code : •3Z

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

CONTROLS/PERSONAL PROTECTION section.

- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Avoid inhalation of vapour or mist.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
- Conditions for safe storage : Keep in properly labelled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	TWA (Mist)	5 mg/m ³	AU OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
2-Ethylhexan-1-ol	104-76-7	TWA	5 ppm	ACGIH
Morpholine	110-91-8	TWA	20 ppm	AU OEL

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

			71 mg/m3	
Further information: Skin absorption				
		TWA	20 ppm	ACGIH

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapour type

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0.45 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : yellow

Odour : characteristic

DIESEL TREATMENT CR - 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 22.06.2024
13.0	09.10.2024	10781510-00018	Date of first issue: 03.04.2013

Odour Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data available

Initial boiling point and boiling range : 100 °C

Flash point : 62 °C
Method: ISO 3679

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : 7 %(V)

Lower explosion limit / Lower flammability limit : 0.5 %(V)

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.831 g/cm³ (20 °C)
Method: DIN 51757

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : 215 °C

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : 2.11 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

DIESEL TREATMENT CR - 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 22.06.2024
13.0	09.10.2024	10781510-00018	Date of first issue: 03.04.2013

Particle characteristics
Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Combustible liquid.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4,951 mg/m3
Exposure time: 4 h

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): \geq 3,160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

2-Ethylhexyl nitrate:

Acute oral toxicity : LD50 (Rat): > 9,600 mg/kg
Acute toxicity estimate: 500 mg/kg
Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Test atmosphere: vapour
Method: Expert judgement

Acute dermal toxicity : LD50 (Rabbit): > 4,800 mg/kg
Acute toxicity estimate: 1,100 mg/kg
Method: Expert judgement

2-Ethylhexan-1-ol:

Acute oral toxicity : LD50 (Rat): 2,047 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0.89 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 1 - 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Remarks: Based on data from similar materials

Morpholine:

Acute oral toxicity : LD50 (Rat): 1,900 mg/kg

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on national or regional regulation.

Acute dermal toxicity : LD50 (Rabbit, male): 500 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rabbit
Result : Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

2-Ethylhexyl nitrate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

2-Ethylhexan-1-ol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Morpholine:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rabbit

DIESEL TREATMENT CR - 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 22.06.2024
13.0	09.10.2024	10781510-00018	Date of first issue: 03.04.2013

Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

2-Ethylhexyl nitrate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

2-Ethylhexan-1-ol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species : Rabbit
Result : Irreversible effects on the eye
Remarks : Based on data from similar materials

Morpholine:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

2-Ethylhexyl nitrate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Morpholine:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

2-Ethylhexyl nitrate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: Ames test
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

2-Ethylhexan-1-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Morpholine:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Hamster
Application Route: Ingestion
Result: negative

Carcinogenicity

Not classified based on available information.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 105 weeks
Result : negative
Remarks : Based on data from similar materials

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

2-Ethylhexan-1-ol:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Morpholine:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 104 weeks
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

2-Ethylhexyl nitrate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

2-Ethylhexan-1-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Morpholine:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: positive
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments., Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

Not classified based on available information.

Components:**2-Ethylhexan-1-ol:**

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:**2-Ethylhexan-1-ol:**

Assessment : No significant health effects observed in animals at concentra-

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

tions of 1 mg/l/6h/d or less.

Repeated dose toxicity**Components:****Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rat
NOAEL : $\geq 1,000$ mg/kg
Application Route : Ingestion
Exposure time : 54 Days
Remarks : Based on data from similar materials

2-Ethylhexyl nitrate:

Species : Rabbit
NOAEL : 500 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

2-Ethylhexan-1-ol:

Species : Rat
NOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Species : Rat
NOAEL : 0.6384 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days
Method : OECD Test Guideline 413

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Morpholine:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 18 Weeks
Remarks : Based on data from similar materials

Species : Rat

DIESEL TREATMENT CR - 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 22.06.2024
13.0	09.10.2024	10781510-00018	Date of first issue: 03.04.2013

NOAEL : 0.543 mg/l
Application Route : inhalation (vapour)
Exposure time : 104 Weeks

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l
aquatic invertebrates : Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000
plants : mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)):
1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOELR (Daphnia magna (Water flea)): > 1 mg/l
aquatic invertebrates (Chron- : Exposure time: 21 d
ic toxicity) : Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

2-Ethylhexyl nitrate:

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): 2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.83 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 1.45 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- EC10 (Desmodesmus subspicatus (green algae)): 1.11 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

2-Ethylhexan-1-ol:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 28.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 39 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.
- Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 16.6 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.
- EC10 (Desmodesmus subspicatus (green algae)): 16.6 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0.43 mg/l
Exposure time: 96 h
Test substance: Neutralised product
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0.1 - 1 mg/l
Exposure time: 48 h
Test substance: Neutralised product
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 1 mg/l
Exposure time: 72 h
Test substance: Neutralised product
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): > 0.1 - 1 mg/l
Exposure time: 72 h
Test substance: Neutralised product
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1 mg/l
Exposure time: 3 h
Test substance: Neutralised product
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Morpholine:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44.5 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 64.63 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Raphidocelis subcapitata (freshwater green alga)): 31.49 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 8.134 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l
Exposure time: 30 min
Method: OECD Test Guideline 209

Persistence and degradability**Components:**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

DIESEL TREATMENT CR - 300ML

Version 13.0 Revision Date: 09.10.2024 SDS Number: 10781510-00018 Date of last issue: 22.06.2024
Date of first issue: 03.04.2013

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

2-Ethylhexyl nitrate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 310

2-Ethylhexan-1-ol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 79 - 99.9 %
Exposure time: 14 d

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Morpholine:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 93 %
Exposure time: 25 d
Method: OECD Test Guideline 301E

Bioaccumulative potential**Components:****2-Ethylhexyl nitrate:**

Bioaccumulation : Species: *Oryzias latipes* (Orange-red killifish)
Bioconcentration factor (BCF): > 500

Partition coefficient: n-octanol/water : log Pow: 5.24
Method: OECD Test Guideline 117

2-Ethylhexan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 2.9

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Partition coefficient: n-octanol/water : log Pow: < 4

DIESEL TREATMENT CR - 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 22.06.2024
13.0	09.10.2024	10781510-00018	Date of first issue: 03.04.2013

Morpholine:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): < 2.8
Method: OECD Test Guideline 305C

Partition coefficient: n-octanol/water : log Pow: -2.55
Method: OECD Test Guideline 107

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(2-Ethylhexyl nitrate, Heptadecenyl imidazoline ethanol)
Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(2-Ethylhexyl nitrate, Heptadecenyl imidazoline ethanol)
Class : 9
Packing group : III
Labels : Miscellaneous

DIESEL TREATMENT CR - 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 22.06.2024
13.0	09.10.2024	10781510-00018	Date of first issue: 03.04.2013

Packing instruction (cargo aircraft)	:	964
Packing instruction (passenger aircraft)	:	964
Environmentally hazardous	:	yes

IMDG-Code

UN number	:	UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Ethylhexyl nitrate, Heptadecenyl imidazoline ethanol)
Class	:	9
Packing group	:	III
Labels	:	9
EmS Code	:	F-A, S-F
Marine pollutant	:	yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations
ADG

UN number	:	UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Ethylhexyl nitrate, Heptadecenyl imidazoline ethanol)
Class	:	9
Packing group	:	III
Labels	:	9
Hazchem Code	:	•3Z
Environmentally hazardous	:	yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION
Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons Standard) Instrument	:	Schedule 5 (Please use the original publication to check for specific uses, specific conditions or threshold limits that might apply for this chemical)
---	---	---

Prohibition/Licensing Requirements	:	There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.
------------------------------------	---	---

DIESEL TREATMENT CR - 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 22.06.2024
13.0	09.10.2024	10781510-00018	Date of first issue: 03.04.2013

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 752 g/l

The components of this product are reported in the following inventories:

AIIC : All ingredients listed or exempt.

SECTION 16: ANY OTHER RELEVANT INFORMATION**Further information**

Revision Date : 09.10.2024

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average
AU OEL / TWA : Exposure standard - time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Develop-

DIESEL TREATMENT CR - 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 22.06.2024
13.0	09.10.2024	10781510-00018	Date of first issue: 03.04.2013

ment; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN