LYTE LADDERS | TOWERS

Professional Trade Extension Ladders

NELT Series

Experience unparalleled safety, comfort, and durability with the UK-made NELT Trade Extension Ladders. Used by industry leading Telecoms companies, the NELT is designed to meet the highest professional standards and exceed your working at height needs.

Key Benefits

- **Heavy-Duty Construction:** Premium-grade aluminium and box section stiles ensures durability for the toughest jobs.
- **Comfortable Climb:** Strengthened D-shaped rungs provide much more comfortable climbing and standing compared to square rungs.
- **Sustainable Design:** UK-sourced Recycled Low-Carbon Aluminium 4.0 rungs, combining durability with environmental responsibility.
- **Safety First:** Advanced stabiliser bar reduces sideways slips, for maximum stability (larger sizes only).
- **Many Size Options:** Available in single, double, and triple sections for various tasks.
- **Maximum Load Capacity:** 150kg - Making it ideal for heavy-duty use.
- **Professional Standard:** Certified to EN131-2 Professional, guaranteeing top-tier quality and reliability.

LYTE EN131 PROFESSIONAL

bsi

MADE IN BRITAIN

Available in 17 sizes

01792 796 666 sales@lyteladders.co.uk lyteladders.co.uk

LYTE LADDERS | TOWERS

Professional Trade Extension Ladders

Specifications

Code	No. of Sections	No. of Rungs Per Section	Weight kg	Closed Length mm	Extended Length mm	Max Standing Height mm*	Approx. Working Height mm*	Stabiliser Width mm
NELT120	Single	7	3.5	2190	2190	1440	3190	N/A
NELT125	Single	8	4.0	2410	2410	1660	3410	N/A
NELT130	Single	10	6.5	2930	2930	2180	3930	N/A
NELT135	Single	12	7.5	3440	3440	2690	4440	1200
NELT140	Single	14	10.0	4070	4070	3320	5070	1200
NELT220	Double	6	9.0	2040	2880	2130	3880	N/A
NELT225	Double	8	10.0	2450	3850	3100	4850	1000
NELT230	Double	10	12.5	2930	4900	4150	5900	1000
NELT235	Double	12	17.0	3455	5970	5220	6970	1000
NELT240	Double	14	18.5	4040	7140	6390	8140	1200
NELT245	Double	15	22.0	4450	7810	7060	8810	1200
NELT250	Double	17	24.5	4950	8880	8130	9880	1200
NELT320	Triple	6	14.5	2040	3720	2520	4270	1000
NELT325	Triple	8	18.5	2450	5230	4480	6230	1000
NELT330	Triple	10	23.0	2930	6920	6170	7920	1200
NELT335	Triple	12	27.0	3455	8480	7730	9480	1200
NELT340	Triple	14	31.0	4040	9660	8910	10660	1200

***Where applicable, the Approx. Working Height is calculated by adding 1750mm (5'8") to the Max Standing Height. This assumes the ladder is positioned at a 75° angle.**

the LADDER ASSOCIATION

PASMA Collective Mark PREFABRICATED ACCESS SUPPLIERS' AND MANUFACTURERS' ASSOCIATION

Achilles UVDB SILVER PLUS

RISQS